

[Read More](#)

**SKU:**

**Price:** ₹650.00

**Stock:** instock

**Categories:** [Chemistry](#)



## Product Description

---



[READ MORE](#)

**SKU:**

**Price:**

**Stock:** instock

**Categories:** [Chemistry](#)

## Product Description

**DESCRIPTION:** Pharmaceutical Refrigerators offer a complete solution for the most demanding requirements for storage of pharmaceuticals, medicines, vaccines, and other temperature-sensitive applications. Model Number : AGN LR-554 External dimensions (W x D x H) : 900 x 650 x 1824mm Internal dimensions (W x D x H) : 800 x 510 x 1425mm Volume : 554L Net weight : 140 (Kg) **Performance** Temperature control range : +2 to +14°C Cooling System : Hermetic rotary compressor 250Watt. **Control** Controller : Microcomputer Control System Temp. Controller : Fan Forced Air circulation. Display : Digital display (in 1°C, 0.1°C increments) Temperature sensor : Thermistor sensor **Refrigeration** Cooling method : Forced cool air circulation Defrost method : Cyclical defrost + forced defrost Refrigerant : R-600a Insulation :

Back Access port diameter : 30mm Casters ; 4 Nos. Interior Illumination : LED Light

**Accessories.** Key : x2. Electrical and Noise Level Power supply : 230V / 50 Hz. Noise level : 42dbA.

## MICRO VOLUME SPECTROPHOTOMETER NANODROP AGN-3101

[Read More](#)

**SKU:**

**Price:**

**Stock:** instock

**Categories:** [Chemistry](#), [Physics](#)



### Product Description

## FEATURES

\* OD600 measurement available 600±8nm. \* Direct, easy to measurements within 5-6 seconds.  
 \* Provided with Inbuilt thermal printer. \* Cuvette port available for cell counting and protein sample detection. \* Software samples including ss DNA, ds DNA, RNA, ds RNA, protein, kinetic cell counting. \* Direct in tube hold be 0.5. **PRODUCT DETAILS:** Wavelength : 200 to 800 nm Wavelength accuracy : 1nm Spectral resolution : ≤3 nm Display : LED Display Touch Screen Absorbance precision : 0.003 Abs Absorbance accuracy : 1% Absorbance range : 0.2-100 A Path length : 0.5, 0.2 and 1 nm Data Output : USB Absorbance range : 0-4A Fluorescent sensitivity : 0.5 pg/ul Fluorescent dynamic range : R2>0.995 Fluorescent repeatability : <1.5%

[Read More](#)

**SKU:**

**Price:**

**Stock:** instock

**Categories:** [Chemistry](#)



## Product Description

### FEATURES

Humidity System 3L stainless-steel pan. Durable triple-wall cabinet construction ensures optimal temperature uniformity. Heated dual pane inner glass door minimizes condensation. CFC-free foam insulated outer door (field- reversible), Magnetic outer door gasket. Chamber Polished stainless-steel interior with coved corners & Stainless-steel shelf. Vali datable in-chamber HEPA air filtration system. Readable in 1% increments includes low RH programmable alarm.

### PRODUCT DETAILS

Capacity - 170-200 L Temperature uniformity -  $\pm 0.2^{\circ}\text{C}$  @  $37^{\circ}\text{C}$  Co2 Concentration Range - 0 to 20% Temperature Range - Ambient  $+5^{\circ}\text{C}$  to  $55^{\circ}\text{C}$  Relative Humidity and Display - Ambient to 95% at  $37^{\circ}\text{C}$  Alarm - Audible/Visual Alarms Filter - HEPA Filter Controller - Microprocessor

## LDF-360L

### FEATURES:

- Less power consumption
- LED Digital Display Temperature Controller
- Highly efficient Longer functional life
- Cleanable & replaceable door magnetic gasket
- Lockable high quality single steel door latch with lock & key
- User friendly design & Easy Setup
- Audio Visual Temperature Alarm for security purpose or power failure



### PRODUCT SPECIFICATIONS: MODEL : AGN-LDF-

**360L** Capacity in liters : 400L Cabinet : Vertical  
Cooling/Refrigerant type : Direct/CFC free  
Interior/Exterior : Exterior made of high-impact, scratch resistant powder coated and Interior SS chamber  
Castors : Heavy duty lockable Ground clearance : 100mm  
Compartments/Racks : 4 nos.  
Temp. Range : -10°C to -25°C increment  $\pm 1^\circ\text{C}$  Noise level : 60dB  
Power Supply : 220/230V at 50Hz **Spares Including:** Power cable and Plug Voltage Stabilizer  
Instruction Manual Warranty Certificate

[Read More](#)

**SKU:**

**Price:**

**Stock:** instock

**Categories:** [Biology](#), [Biotechnology](#), [Chemistry](#), [Histopathology](#), [Laboratory Equipments](#), [Pathology](#), [Pharmacy](#)

## Product Description

specimens & blood samples. To manufacture the equipments, we use finest quality materials sources from the most reliable vendors. The clients can avail our Deep Freezer Vertical Upright in different customized models and specifications as per requirements.

## Hot Air Oven AGN-101H

[Read More](#)

**SKU:**

**Price:** ₹315,000.00 Original price was: ₹315,000.00. ₹280,000.00 Current price is: ₹280,000.00.

**Stock:** instock

**Categories:** [Biology](#), [Biotechnology](#), [Chemistry](#), [Entomology](#), [Laboratory Equipments](#), [Pathology](#), [Pharmacy](#)



### Product Description

- Capacity: more than 300 liters.
- Double wall SS304 with glass wool insulation.
- Solid and plain bottom without electricals.
- Interior made out of polished Stainless Steel sheet 304 grade.
- Exterior made out of Stainless steel sheet 304 grade.
- Easily removable SS 304 trays with adjustable height in 25mm.
- Microprocessor based PID Digital Temperature controller LED display shows temperature & time.
- Door with heavy brass chrome plated hinges, quick magnetic locking facility.
- Inside Temperature ambient to +50°C to 250°C with accuracy  $\pm 2^{\circ}\text{C}$ .
- PT100 temperature sensor.
- Audio Visual Temperature for over/undershoot temperature, door opening and security purpose.
- Forced air circulation fan for uniform temperature.
- SS tubular heater.
- Automatic daily data backup.
- CE & ISO Certified.
- Works on 220/230 VAC at 50Hz single phase.



[Read More](#)

**SKU:**

**Price:** ₹115,000.00 Original price was: ₹115,000.00. ₹105,000.00 Current price is: ₹105,000.00.

**Stock:** instock

**Categories:** [Biology](#), [Biotechnology](#), [Chemistry](#), [Entomology](#), [Laboratory Equipments](#), [Pathology](#), [Pharmacy](#)

## Product Description

- Capacity: 150 litre.
- Glass wool insulation.
- External Dimension: 710x651x870mm.
- Internal Dimension: 600x500x500mm.
- Interior made out of polished Stainless Steel sheet.
- Exterior made out of cold rolled steel plate with melamine resin baking finish.
- Shelf plate with standard load approx. 15kgs/piece
- Easily removable SS 304 trays with adjustable height.
- Microprocessor PID Digital 3 patterns Temperature controller LCD/LED display.
- Door with heavy brass chrome plated hinges, quick magnetic locking facility and Scirocco fan.
- Inside Temperature ambient to +10°C to 250°C with accuracy  $\pm 2.5^{\circ}\text{C}$ , temp control  $+1^{\circ}\text{C}$ .
- Safety counter measures: self diagnosis functions (temp sensor abnormal, heater disconnection, SSR-short Automatic overheating prevention).
- Key lock function, over heat prevention, electrical leakage breaker with over current protection. SS heater 1.34KW and 30W blower motor fan.
- CE & ISO Certified.
- Works on 220/230 VAC at 50Hz single phase.



[READ MORE](#)

**SKU:**

**Price:** ₹120,000.00 Original price was: ₹120,000.00. ₹110,000.00 Current price is: ₹110,000.00.

**Stock:** instock

**Categories:** [Biology](#), [Biotechnology](#), [Chemistry](#), [Entomology](#), [Histopathology](#), [Laboratory Equipments](#), [Pathology](#), [Pharmacy](#)

## Product Description

- Capacity: more than 150 litre bench top model.
- Interior made out of polished Stainless Steel sheet.
- Exterior made out of (CRCA) Mild Steel powder coated paint.
- Chrome plated rack, load capacity 10kg.
- 3 nos. easily removable SS 304 trays with adjustable height.
- Automatic Microprocessor programmable PID Digital Temperature controller with timer, alarm & auto tuning.
- Door with glass window fluoroelastomer gasket, heavy brass chrome plated hinges, quick magnetic locking facility and Two adjustable exhaust Air flap.
- Inside Temperature ambient to +5°C to 300°C with accuracy  $\pm 0.5^{\circ}\text{C}$ , uniformity  $\pm 2.0^{\circ}\text{C}$  at 100°C.
- Temperature safety device (DIN 12880) with visual alarm.
- Aero dynamic internal design for achieving horizontal air circulation.
- Automatic cut off of heater & blower and USB Interface.
- CE & ISO Certified.
- Works on 220/230 VAC at 50Hz single phase.



**Price:** ₹350,000.00 Original price was: ₹350,000.00. ₹  
325,000.00 Current price is: ₹325,000.00.

**Stock:** instock

**Categories:** [Biology](#), [Biotechnology](#), [Chemistry](#),  
[Histopathology](#), [Hospital Furniture](#), [Laboratory  
Equipments](#), [Pathology](#), [Pharmacy](#)

## Product Description

**FROST FREE DEEP FREEZER (AGN-DF-720L-30C) Technical Specifications** • Refrigerator Type: Upright freezer with shelves • Temperature: -20° C or better • Microprocessor controller • Display - Digital • Capacity: 640 Liters (Approximate) • Defrosting Type: Frost Free (Automatic defrosting facility) • Alarm: Temperature-high/low, door open, power cut, malfunction • ISO & CE certified • Power: 230V, 50/ 60Hz • Warranty: 1 year

---



[Read More](#)

**SKU:**

**Price:** ₹950,000.00 Original price was: ₹950,000.00. ₹750,000.00 Current price is: ₹750,000.00.

**Stock:** instock

**Categories:** [Biology](#), [Biotechnology](#), [Chemistry](#), [Laboratory Equipments](#)

## Product Description

CE certified Capacity in liters: 501-550 L Type of Cabinet: Vertical Heavy duty lockable castors and levelling for adjustments and installation 15 Nos. of holding racks 4 Nos. of inner storage compartments with insulated doors and adjustable height Dual compressor 2 Nos. of corrosion resistant racks One Pair of Cryogloves One nos. of Ice scraper provided Temperature Chart recorder USB port



**Price:** ₹300,000.00 Original price was: ₹300,000.00. ₹  
270,000.00 Current price is: ₹270,000.00.

**Stock:** instock

**Categories:** [Chemistry](#), [Laboratory Equipments](#)

## Product Description

**Laboratory Refrigerator** *Salient Features:* Temperature range +2°C to +8°C Capacity 500 Litres Inner cabinet made of SS304 Outer cabinet made of powder-coated sheet Inner shelves made of SS304 CFC free, eco-friendly refrigerant (R134a) Cyclopentain foaming PUF insulation No frost, fan-assisted cooling circulation system Ultra-fast pull-down times, auto defrost with a self-evaporating drip tray front to rear hot air anti-condensation a digital temperature controller Double grazed safety glass doors Low noise and green technology, energy-saving technology full-length elimination fitted with caster wheels, front two with brakes self-closing hinge doors with locks as standard Input 220-240V, 50Hz with power code and plug circular chart temperature recorder USB port 45mm dia Automatic voltage stabilizer with time delay restart

[Read More](#)

**SKU:**

**Price:** ₹375,000.00 Original price was: ₹375,000.00. ₹350,000.00 Current price is: ₹350,000.00.

**Stock:** instock

**Categories:** [Chemistry](#)



## Product Description

It comes with modern and sophisticated features, one of which is its capacity to show rapid temperature and humidity changes according to input settings. They can cool down impressively, with high precision, enabling you to carry out complex climate tests. Through the digital display (Temperature, weekdays, time, humidity, automatic fan speed, programer status and set-up values-language) with Audio-Visual Alarm you can see all the parameters such as temperature inside as well as the humidity levels. The ingenuity of the design that it is capable of stable operation over long periods of time, even in situations wherein the illuminated chambers are filled with samples. **Its features include:**

- International quality standards and suitable for most of environmental conditions
- These Environmental Chamber are doubled walled constructed and has proper locking arrangement for SS 304 door is capable of simulating a wide rage of temperature and humidity conditions with Polystyrene Foam insulated.
- Compact in designed which enables you to place it in small space and use with ease.
- Is designed according to international quality standards hence you can be rest assured of high quality performance.
- Inclusive of secure locking system so that contents are safe and secure inside.
- Humidity inside is created with steam injected into the working chamber.
- Energy efficient and show safe and reliable performance in maintaining temperature as required in

steel (0.8 mm thickness) to ensure that they do not get worn out with extensive usage. Exterior made of GI Steel Sheet with epoxy coated. **Technical Specifications:** Capacity : 37 liters Inner dimension : 410w x 300d x 300h Exterior dimension : 758w x 645d x 1110h Display : Programmable digital touch screen Shelves : SS Wire Mesh Refrigerant : CFC Free R-404 non flammable (hermetically sealed single stage refrigeration system Temperature Range : -20°C to +150°C ±0.2°C Humidity Range : 20% to 98% ±1% Access Port : Dia 50mm Pull Down time : +40°C to 20°C within 35 mins Heat up time : -20°C to +150°C within 35 mins Water Tank Capacity : 5 liters Calibration : Yes Data Logger : Yes Works on : 220/240VAC, Single Phase