

MODEL) 4 Stroke 1 Cylinder

[Read More](#)

SKU:

Price: ₹42,000.00

Stock: instock

Categories: [Applied Mechanics](#)



Product Description

Rear Axle With Differential Gear

[Read More](#)

SKU:

Price: ₹42,000.00

Stock: instock

Categories: [Applied Mechanics](#)





AGN ENTERPRISES

MANUFACTURER & SUPPLIER
ALL KINDS OF LABORATORY EQUIPMENTS



[Read More](#)

SKU:

Price: ₹42,000.00

Stock: instock

Categories: [Biology](#)



Product Description

Price: ₹40,500.00

Stock: instock

Categories: [Biology](#)



Product Description



WATER STILL
SHEATHED
Model No. S
(approx) 4.0
Water Cons
Power Ratin

Water stills are carefully designed to produce high purity pyrogen free distilled water. They are made from 3.3 exp. grade stainless steel. The horizontal type boiler is a compact design, silica sheathed, mounted on a stand and clamps. It is

45°C which is ensured by an efficient

- The stand is powder coated for rust free operation and lustrous
- The unit automatically switches off if water level in the boiler falls below heater.
- Cooling water from the condenser is re-circulated into the boiling chamber, hence saving
- Drain nozzle/Tap on Stop Cork is provided for easy cleaning and maintenance.
- Electrical Power: 220/240 V, 50/60Hz, Single Phase

Unique Feature:

This model is equipped with in-built water level sensor of water failure or overheating and buzzer is provided.

[Read More](#)

SKU:

Price: ₹40,000.00

Stock: instock

Categories: [Water Still/Distillation Unit](#)

Product Description

Water stills are carefully designed to produce high purity pyrogen free distilled water. The water still made from 3.3 exp. borosilicate glass comprises of horizontal type boiler, condenser, constant level device, silica sheathed (Quartz) heater, along with stand and clamps. Features:

- Borosilicate condenser and boiler are fitted with a removable silica sheathed heater and screw threaded connectors for ease of Cleaning.
- Distillate temperature is approx. between 25° to 45°C which is ensured by an efficient
- The stand is powder coated for rust free operation and lustrous
- The unit automatically switches off if water level in the boiler falls below heater.
- Cooling water from the condenser is re-circulated into the boiling chamber, hence saving

This model is equipped with in built water level sensor to protect the glass parts in case of water failure or overheating and buzzer is provided when user attention is required

HUMIDITY CABINET Digital Combined Controller for Temp. & Humidity



(Inner S.S) Temp 5 deg C above ambient to 60 deg C.
Humidity 30-90%

[Read More](#)

SKU:

Price: ₹40,000.00

Stock: instock

Categories: [Biotechnology](#)

Product Description

(Inner S.S) Temp 5 deg C above ambient to 60 deg C. Humidity 30-90%

Price: ₹40,000.00

Stock: instock

Categories: [Metallurgy](#)



Product Description

BELT GRINDER/ BELT POLISHER “AGN Make”

Designed For Initial Rough Grinding of Specimens/metals. Works on 220V in Single Phase. Manual Belt -100/915mm Endless Belt Pulleys, Balanced Pulleys & Polishing Motor Power ½ HP

[Read More](#)

SKU:

Price: ₹40,000.00

Stock: instock

Categories: [Metallurgy](#)



AUTOCLAVE (Vertical) Double Wall 250 x 450mm, 22 Ltr.

[Read More](#)

SKU:

Price: ₹40,000.00

Stock: instock

Categories: [Pharmacy](#)



Product Description

SLIDE WARMING TABLE

It is rectangular in shape and used to heat slides at a uniform temperature just below the melting point of wax so as to provide flattening without any damage to the section. The top plate is securely mounted on a insulated metal base. Technical Specifications ● Temperature Range : ambient to 90 Degree ● Hot Plate Dimensions (Inch) : 12x10 Supplied complete with cord and plug and is suitable to work on 220/230V-AC Supply

[Read More](#)

SKU:

Price: ₹39,000.00

Stock: instock

Categories: [Histopathology](#)



required durability. Technical Specifications ● Temperature Range: ambient to 99 Deg C ● Overall Dimensions (mm) : 320x320x110 ● Plate Dimensions (mm) : 340 x 225 ● Power : 200VA Supplied complete with the power cord.

TISSUE FLOTATION BATH



It is microprocessor controlled, incorporates a feather touch keypad with 7 segment display along with the precise temperature control for setting the floatation bath temperature. It has an in-built memory to store the set temperature. The bath is made up of corrosion resistance material to provides the required durability. Technical Specifications ● Water Temperature Range: ambient to 99 Deg C ● Overall Dimensions (mm) : 320x320x110 ● Water Bath Dimensions,inner (mm) : 238x180 ● Power : 200VA Supplied complete with the power cord.

[Read More](#)

SKU:

Price: ₹39,000.00

Stock: instock

Categories: [Histopathology](#)

Product Description

It is microprocessor controlled, incorporates a feather touch keypad with 7 segment display along with the precise temperature control for setting the floatation bath temperature. It has an in-built memory to store the set temperature. The bath is made up of corrosion resistance material to provides the required durability. Technical Specifications ● Water Temperature Range: ambient to 99 Deg C ● Overall Dimensions (mm) : 320x320x110 ● Water Bath Dimensions,inner (mm) : 238x180 ● Power : 200VA Supplied complete with the power cord.

10"x5"x5" (250x125x125mm)

[Read More](#)



SKU:

Price: ₹39,000.00

Stock: instock

Categories: [Biotechnology](#)

Product Description