

ROCK & MINERAL SET (PM= Paper Mounted , PS= Polished Showcase)

[Read More](#)

SKU:

Price: ₹950.00

Stock: instock

Categories: [Geography & Surveying](#)



Product Description

ROCK & MINERAL SET (PM= Paper Mounted , PS= Polished Showcase)

(Any One Chart as Below) Educational Chart
(72x100CM)

[Read More](#)

SKU:

Price: ₹3,800.00

Stock: instock

Categories: [Geography & Surveying](#)



Product Description

(Any One Chart as Below) Educational Chart (72x100CM)

ROD & FRAME APPARATUS

[Read More](#)

SKU:

Price: ₹26,000.00

Stock: instock

Categories: [Psychology](#)



Roman Number With The Help Of Roman Numerical Printed Tiles

[Read More](#)

SKU:

Price: ₹1,150.00

Stock: instock

Categories: [Mathematics](#)



Product Description

ROOT PRESSURE APPARATUS (Borosilicate Glass)


[Read More](#)

SKU:

Price: ₹300.00

Stock: instock

Categories: [Biology](#)



Product Description

Price: ₹1,400.00

Stock: instock

Categories: [Applied Mechanics](#)



Product Description

ROTA ROD WITH DIGITAL TIMER Four Compartment

[Read More](#)

SKU:

Price: ₹16,000.00

Stock: instock

Categories: [Pharmacy](#)



Product Description



[Read More](#)

SKU:

Price: ₹6,000.00

Stock: instock

Categories: [Pharmacy](#)

Product Description

ROTA ROD WITH DIGITAL TIMER Three Compartment



[Read More](#)

SKU:

Price: ₹14,000.00

Stock: instock

Categories: [Pharmacy](#)

Product Description

ROTA ROD WITH DIGITAL TIMER Two Compartment



[Read More](#)

SKU:

Price: ₹13,000.00

Stock: instock

Categories: [Pharmacy](#)

Product Description

[Read More](#)

SKU:

Price:

Stock: instock

Categories: [Uncategorized](#)



Product Description

Specification :- Type : Electronic lift Temperature range : Ambient to 220°C Heating power : 1500W. Operating voltage : 220 – 240 V at 50/60 HZ Display : LCD display Temperature deviation : at 2°C. Rotation speed : adjustment 20 to 280 RPM. **Features :-** - Cordless power supply allows emptying and refilling of water bath without unplugging. - LCD display indicates set and actual values of heating bath temperature, rotation speed, and lift height adjustment. - Auto lift from heating bath at the time of power failure - Accommodate flask size from 50 ml to 5000 ml. - Multifunction comb clip - A plastic coating on glass (P+G) - Condensate trap to trap external moisture formed on condenser - Provided with flask of 1000 ml each flask with flask joint SJ29/32 - Evaporation flask feeding via stopcock. - Rust free body material - Infrared bi-directional communication between heating bath and rotary evaporator **Vacuum Pump :** Operating voltage : 220 – 240 V at 50/60 HZ Membrane Pump : Two stage PTFE with window heads Flow rate : 1.8 m³/hr. Vacuum : 5 mbar **Vacuum Controller :** Display : Touch screen Operating mode : Manual, Timer, Continuous, Drying etc. **Features :-** - Rotary knob / button Allows in both ways - Built in solvent library (extended version: 60 Solvents). - Allows to add and

ROTARY MICROTOME



It is designed to enhance manual sectioning. It is based on cross roller guides with high precision screw which provides accuracy and stability for sectioning. This Microtome has been designed for effortless manual sectioning using counter balanced handwheel. The spacious section waste tray collects sectioning waste during trimming and sectioning. **Salient**

Features ● Based on cross roller guides ● Handwheel lockable at any position ● High precision specimen feed ● Lateral adjustment of knife holder ● Ergonomically located handwheel for coarse advance ● Counter balanced handwheel **Technical**

Specification ● Section Thickness Setting Range: 0.5-60µm ● Setting Values: 0.5-2µm increment step 0.5µm ● 2-20µm increment step 1µm ● 20-60µm increment step 5µm ● Minimum setting value :0.5µm Supplied complete as above with disposable blade holder assembly suitable for low & high profile blades & sample pack of disposable blades

[Read More](#)

SKU:

Price: ₹350,000.00

Stock: instock

Categories: [Histopathology](#)

Product Description

It is designed to enhance manual sectioning. It is based on cross roller guides with high precision screw which provides accuracy and stability for sectioning. This Microtome has been designed for effortless manual sectioning using counter balanced handwheel. The spacious



AGN ENTERPRISES

MANUFACTURER & SUPPLIER
ALL KINDS OF LABORATORY EQUIPMENTS



Range: 0.5-60 μ m ● Setting values: 0.5-2 μ m increment step 0.5 μ m ● 2-20 μ m increment step 1 μ m ● 20-60 μ m increment step 5 μ m ● Minimum setting value :0.5 μ m Supplied complete as above with disposable blade holder assembly suitable for low & high profile blades & sample pack of disposable blades