



SKU:

Price: ₹6,300.00

Stock: instock

Categories: [Applied Mechanics](#)

Product Description

SIMPLE PENDULUM APPARATUS 10" long with 18mm brass bob (Light Pattern)

[Read More](#)

SKU:

Price: ₹280.00

Stock: instock

Categories: [Physics](#)



Product Description

[Read More](#)

SKU:

Price: ₹140.00

Stock: instock

Categories: [Biology](#)



Product Description

Simple Wall Type with Rollers, Projector Screen Size 70"x50"

[Read More](#)

SKU:

Price: ₹1,400.00

Stock: instock

Categories: [Visual Teaching](#)



Product Description



[Read More](#)

SKU:

Price: ₹1,100.00

Stock: instock

Categories: [Visual Teaching](#)

Product Description

SINGLE COM MICROTOM



It has LCD display v
and it has motorize
thickness can be se
sealed compressor
accurate temperatu
operation. User can
with the section thi
window to prevent
closed drainage sys
condensed and defr

Features ● Motor
Alarm to indicate th
display. ● Large Sta
adequate storage f
●Section thickness
size 40x50mm ●Te
●Specimen Vertica



AGN ENTERPRISES

MANUFACTURER & SUPPLIER
ALL KINDS OF LABORATORY EQUIPMENTS



SKU:

Price: ₹630,000.00

Stock: instock

Categories: [Histopathology](#)

Product Description

It has LCD display which displays the set parameters and it has motorized coarse feed and the section thickness can be set with the help of knob. It has sealed compressor to ensure proper cooling and accurate temperature control to ensure trouble free operation. User can easily set the section thickness with the section thickness knob. Electrically heated window to prevent frost formation. Equipped with a closed drainage system to ensure collection of condensed and defrost fluids in container. **Salient Features** ● Motorized forward and backward. ● Alarm to indicate the end of travel. ● Easy to read LCD display. ● Large Stainless Steel chamber provides adequate storage facility. **Technical Specifications:** ●Section thickness: 1-30 μ m in 1 μ m steps ●Section size 40x50mm ●Temperature range : up to -40° C ●Specimen Vertical stroke : 60mm ●Specimen Horizontal Stroke: 20mm Supplied complete with knife holder, razor 120mm long with back handle, dust cover & operational manual

Make”

[Read More](#)



SKU:

Price: ₹7,800.00

Stock: instock

Categories: [Visual Teaching](#)

Product Description

SINGLE PAN ANALYTICAL BALANCE (Dhona Type) (SIGMA Make) Cap. 200 gms, L.C 0.1 mg

[Read More](#)

SKU:

Price: ₹20,000.00

Stock: instock

Categories: [Chemistry](#)



Product Description

Price: ₹5,500.00

Stock: instock

Categories: [Applied Mechanics](#)



Product Description

SINGLE STAGE BEVEL GEARS MODEL

[Read More](#)

SKU:

Price: ₹6,000.00

Stock: instock

Categories: [Applied Mechanics](#)



MODEL


[Read More](#)

SKU:

Price: ₹6,000.00

Stock: instock

Categories: [Applied Mechanics](#)



Product Description

SINGLE STAGE DISTILLATION (Model)

Features

- Distillate temperature controlled by efficient condenser
- operation lustrous
- Cooling water inlet into boiling chamber
- provided in fluorescent
- Electrical Power Phase Supply.
- Boiler is provided with Constant Level cleaning of boiler



Unique Feature This temperature switch of water failure or c

- Gate Valve : Conserves cooling water wastage in case of power
- Flow Switch : In-built safety feature for the equipment unit sh

Borosilicate Condenser

	Output Capacity (Approx.)	Power Rating (Total)
SD-20BH	2 Ltr/Hr	1.7 KW
SD-50BH	5 Ltr/Hr	3.4 KW

Quartz Condenser

	Output Capacity (Approx.)	Power Rating (Total)
SD-20QH	2 Ltr/Hr	1.7 KW
SD-50QH	5 Ltr/Hr	3.4 KW

[Read More](#)

SKU:

Price: ₹50,000.00

Stock: instock

Categories: [Water Still/Distillation Unit](#)

Product Description

Features

- Distillate temperature is between ensured by an efficient condenser.
- operation lustrous in boiler
- Cooling water from the condenser re-circulated into boiling chamber, hence saving energy.
- provided in fluctuation
- Electrical Power : 220/240 V, 50/60Hz, Single Phase Supply.
- Boiler is provided with Replaceable Quartz ConstantLevel Device for easy draining and cleaning of boiling chamber.

Unique Feature This model is equipped with in-built temperature switch to protect the Glass parts in case of water failure or overheating.

- Gate Valve : Conserves cooling water wastage in case of power failure.
- Flow Switch : In-built safety feature for the equipment unit shut off in case of cooling water failure.

Borosilicate Condenser

	Output Capacity (Approx.)	Power Rating (Total)	Cooling Water Consumption (App.)	
SD-20BH	2 Ltr/Hr	1.7 KW	35 Ltr/Hr	50000.00
SD-50BH	5 Ltr/Hr	3.4 KW	70 Ltr/Hr.	80000.00

Quartz Condenser

	Output Capacity (Approx.)	Power Rating (Total)	Cooling Water Consumption (App.)	
SD-20QH	2 Ltr/Hr	1.7 KW	35 Ltr/Hr	64000.00
SD-50QH	5 Ltr/Hr	3.4 KW	70 Ltr/Hr.	120000.00