



**SKU:**

**Price:** ₹6,300.00

**Stock:** instock

**Categories:** [Applied Mechanics](#)

## Product Description

### SIMPLE PENDULUM APPARATUS 10" long with 18mm brass bob (Light Pattern)

[Read More](#)

**SKU:**

**Price:** ₹280.00

**Stock:** instock

**Categories:** [Physics](#)



## Product Description

[Read More](#)

**SKU:**

**Price:** ₹140.00

**Stock:** instock

**Categories:** [Biology](#)



## Product Description

### Simple Wall Type with Rollers, Projector Screen Size 70"x50"

[Read More](#)

**SKU:**

**Price:** ₹1,400.00

**Stock:** instock

**Categories:** [Visual Teaching](#)



## Product Description



[Read More](#)

**SKU:**

**Price:** ₹1,100.00

**Stock:** instock

**Categories:** [Visual Teaching](#)

## Product Description

## SINGLE COM MICROTOM



It has LCD display v  
and it has motorize  
thickness can be se  
sealed compressor  
accurate temperatu  
operation. User can  
with the section thi  
window to prevent  
closed drainage sys  
condensed and defr

**Features** ● Motor  
Alarm to indicate th  
display. ● Large Sta  
adequate storage f  
●Section thickness  
size 40x50mm ●Te  
●Specimen Vertica



# AGN ENTERPRISES

MANUFACTURER & SUPPLIER  
ALL KINDS OF LABORATORY EQUIPMENTS



**SKU:**

**Price:** ₹630,000.00

**Stock:** instock

**Categories:** [Histopathology](#)

## Product Description

It has LCD display which displays the set parameters and it has motorized coarse feed and the section thickness can be set with the help of knob. It has sealed compressor to ensure proper cooling and accurate temperature control to ensure trouble free operation. User can easily set the section thickness with the section thickness knob. Electrically heated window to prevent frost formation. Equipped with a closed drainage system to ensure collection of condensed and defrost fluids in container. **Salient Features** ● Motorized forward and backward. ● Alarm to indicate the end of travel. ● Easy to read LCD display. ● Large Stainless Steel chamber provides adequate storage facility. **Technical Specifications:** ●Section thickness: 1-30µm in 1µm steps ●Section size 40x50mm ●Temperature range : up to -40° C ●Specimen Vertical stroke : 60mm ●Specimen Horizontal Stroke: 20mm Supplied complete with knife holder, razor 120mm long with back handle, dust cover & operational manual

## Make”

[Read More](#)



**SKU:**

**Price:** ₹7,800.00

**Stock:** instock

**Categories:** [Visual Teaching](#)

## Product Description

## SINGLE PAN ANALYTICAL BALANCE (Dhona Type) (SIGMA Make) Cap. 200 gms, L.C 0.1 mg

[Read More](#)

**SKU:**

**Price:** ₹20,000.00

**Stock:** instock

**Categories:** [Chemistry](#)



## Product Description

**Price:** ₹5,500.00

**Stock:** instock

**Categories:** [Applied Mechanics](#)



## Product Description

### SINGLE STAGE BEVEL GEARS MODEL

[Read More](#)

**SKU:**

**Price:** ₹6,000.00

**Stock:** instock

**Categories:** [Applied Mechanics](#)



## MODEL


[Read More](#)

**SKU:**

**Price:** ₹6,000.00

**Stock:** instock

**Categories:** [Applied Mechanics](#)



## Product Description

## SINGLE STAGE DISTILLATION Model)

### Features

- Distillate temperature control with efficient condenser
- operation lustrous
- Cooling water inlet into boiling chamber
- provided in fluorescent
- Electrical Power Phase Supply.
- Boiler is provided with Constant Level cleaning of boiler



Unique Feature This apparatus has a temperature switch that cuts off the power in case of water failure or c



- Gate Valve : Conserves cooling water wastage in case of power
- Flow Switch : In-built safety feature for the equipment unit sh

## Borosilicate Condenser

	Output Capacity (Approx.)	Power Rating (Total)
SD-20BH	2 Ltr/Hr	1.7 KW
SD-50BH	5 Ltr/Hr	3.4 KW

## Quartz Condenser

	Output Capacity (Approx.)	Power Rating (Total)
SD-20QH	2 Ltr/Hr	1.7 KW
SD-50QH	5 Ltr/Hr	3.4 KW

[Read More](#)

**SKU:**

**Price:** ₹50,000.00

**Stock:** instock

**Categories:** [Water Still/Distillation Unit](#)

## Product Description

### Features

- Distillate temperature is between ensured by an efficient condenser.
- operation lustrous in boiler
- Cooling water from the condenser re-circulated into boiling chamber, hence saving energy.
- provided in fluctuation
- Electrical Power : 220/240 V, 50/60Hz, Single Phase Supply.
- Boiler is provided with Replaceable Quartz ConstantLevel Device for easy draining and cleaning of boiling chamber.

Unique Feature This model is equipped with in-built temperature switch to protect the Glass parts in case of water failure or overheating.



- Gate Valve : Conserves cooling water wastage in case of power failure.
- Flow Switch : In-built safety feature for the equipment unit shut off in case of cooling water failure.

## Borosilicate Condenser

Output Capacity (Approx.)		Power Rating (Total)	Cooling Water Consumption (App.)	
SD-20BH	2 Ltr/Hr	1.7 KW	35 Ltr/Hr	50000.00
SD-50BH	5 Ltr/Hr	3.4 KW	70 Ltr/Hr.	80000.00

## Quartz Condenser

Output Capacity (Approx.)		Power Rating (Total)	Cooling Water Consumption (App.)	
SD-20QH	2 Ltr/Hr	1.7 KW	35 Ltr/Hr	64000.00
SD-50QH	5 Ltr/Hr	3.4 KW	70 Ltr/Hr.	120000.00