



Cap. 147 Ltr.

(Inner S.S) Temp 5 deg C above ambient to 60 deg C.
Humidity 30-90%

[Read More](#)

SKU:

Price: ₹68,000.00

Stock: instock

Categories: [Biotechnology](#)

Product Description

(Inner S.S) Temp 5 deg C above ambient to 60 deg C. Humidity 30-90%

INCUBATOR B.O.D. Inner Chamber Size 505 x 451 x 830 mm, Cap. 6cu. Ft. or 171 Ltr. Material Al.

[Read More](#)

SKU:

Price: ₹68,000.00

Stock: instock

Categories: [Biotechnology](#)



Product Description

[Read More](#)

SKU:

Price: ₹69,000.00

Stock: instock

Categories: [Biology](#)



Product Description

DIGITAL POLARIMETER “AGN Make

[Read More](#)

SKU:

Price: ₹70,000.00

Stock: instock

Categories: [Physics](#)



Product Description



[Read More](#)

SKU:

Price: ₹70,000.00

Stock: instock

Categories: [Pharmacy](#)

Product Description

HUMIDITY CABINET Inside Chamber 605 x 605 x 605mm, Cap. 225 Ltr.



(Inner S.S) Temp 5 deg C above ambient to 60 deg C.
Humidity 30-90%

[Read More](#)

SKU:

Price: ₹70,000.00

Stock: instock

Categories: [Biotechnology](#)

Product Description

(Inner S.S) Temp 5 deg C above ambient to 60 deg C. Humidity 30-90%



appearance but incorporates more advance technology and use of selected alloys for manufacturing of individual components as per International Standards. It has a feed range of 1 to 50 microns, is controlled through latest CAM DRIVE SYSTEM in precise steps of 1 micron with razor length 120mm with back & handle is fabricated from imported fine grain steel alloy tested for micro structure and is heat treated to maintain optimum strength and sharpness. A full swinging protective cover is provided for easier cleaning and lubrication Supplied complete with object holder, dust cover, oil can, knife 120mm & honing stone

[Read More](#)

SKU:

Price: ₹70,000.00

Stock: instock

Categories: [Histopathology](#)

Product Description

(Latest "Spencer" 820-Type) Specifically Designed for export and is similar to model MRM1120 in design and appearance but incorporates more advance technology and use of selected alloys for manufacturing of individual components as per International Standards. It has a feed range of 1 to 50 microns, is controlled through latest CAM DRIVE SYSTEM in precise steps of 1 micron with razor length 120mm with back & handle is fabricated from imported fine grain steel alloy tested for micro structure and is heat treated to maintain optimum strength and sharpness. A full swinging protective cover is provided for easier cleaning and lubrication Supplied complete with object holder, dust cover, oil can, knife 120mm & honing stone



Cap. (approx) Cooling Water 150 ltr/h, P

Water stills are care
purity pyrogen free
made from 3.3 exp
horizontal type boi
device, silica sheath
stand and clamps. I

- Borosilicate co
removable silic
threaded conn
- Distillate temp
45°C which is
- The stand is po
and lustrous a
- The unit auton
in the boiler fa
- Cooling water
into the boiling
- Drain Stop Cor
maintenance.
- Electrical Powe
Phase Supply.
equipped with
protect the Gla
overheating an
attention is re

Technical Specifica
Distillate Quality Py



Categories: [Water Still/Distillation Unit](#)

Product Description

Water stills are carefully designed to produce high purity pyrogen free distilled water. The water still made from 3.3 exp. borosilicate glass comprises of horizontal type boiler, condenser, constant level device, silica sheathed (Quartz) heater, along with stand and clamps. **Features:**

- Borosilicate condenser and boiler are with a removable silica sheathed heater and screw threaded connectors for ease of Cleaning.
- Distillate temperature is approx. between 25° to 45°C which is ensured by an condenser.
- The stand is powder coated for rust free operation and lustrous appearance.
- The unit automatically switches off if water level in the boiler falls below heater.
- Cooling water from the condenser is re-circulated into the boiling chamber, hence saving energy.
- Drain Stop Cork is provided for easy cleaning and maintenance.
- Electrical Power: 220/240 V, 50/60Hz, Single Phase Supply. **Unique Feature:** This model is equipped with in-built water level sensor to protect the Glass parts in case of water failure or overheating and buzzer is provided when user attention is required

Technical Specification Conductivity 0.8 to 1 $\mu\text{S}/\text{cm}$ Distillate Quality Pyrogen Free

Price: ₹72,000.00

Stock: instock

Categories: [Biology](#)



Product Description

Power Steering System

[Read More](#)

SKU:

Price: ₹72,000.00

Stock: instock

Categories: [Applied Mechanics](#)



HORIZONTAL UNIT 120x60x60cm



Structure made of thick ply board with sunmica from outside & S.S. Workbench. Clear acrylic side panels & front door. HEPA Filter efficiency 99.97% upto 0.3 micron.

[Read More](#)

SKU:

Price: ₹74,000.00

Stock: instock

Categories: [Pharmacy](#)

Product Description

Structure made of thick ply board with sunmica from outside & S.S. Workbench. Clear acrylic side panels & front door. HEPA Filter efficiency 99.97% upto 0.3 micron.

Research Model Half Shade, 400mm tube



[Read More](#)

SKU:

Price: ₹76,000.00

Stock: instock

Categories: [Physics](#)

Product Description