



Capacity 50 Ltr/Hr , Consists of two plastic column charged with high exchange capacity Cation & Anion resins. Conductivity Meter Provided

[Read More](#)

SKU:

Price: ₹24,000.00

Stock: instock

Categories: [Pharmacy](#)

Product Description

Capacity 50 Ltr/Hr , Consists of two plastic column charged with high exchange capacity Cation & Anion resins. Conductivity Meter Provided

FOR SIZE 22X15CM WE CHARGE 450.00 RS ONLY

[Read More](#)

SKU:

Price: ₹1,200.00

Stock: instock

Categories: [Geography & Surveying](#)



Product Description

For Size 22x15cm we Charge 450.00 Rs only

WATER LEVEL APPARATUS on Base

[Read More](#)

SKU:

Price: ₹130.00

Stock: instock

Categories: [Physics](#)



Product Description

Price: ₹450.00

Stock: instock

Categories: [Chemistry](#)



Product Description

WATER STILL HEATER

It comprises of horizontal coil with a 3 KW chromi cutoff, highly efficient output of single dist safe to operate and



- Abundant Output of distilled water for Laboratory use
- Distillate temperature 40° C which is safe to operate and

Construction

- The stand is powder coated for long and rust free operation.
- The boiler and condenser are designed for high efficiency.
- Boiler is provided with Teflon Screw Cork for easy draining and cleaning of boiling chamber.
- Screw Threaded Connectors : These are provided for easy plumbing Et Installation to avoid any glassware breakage during assembly.
- For use on 220/240 V, 50/60Hz, Single Phase Supply.

Additional Optional Accessories (At Extra Cost)

- Gate Valve : Conserves cooling water wastage in case of power failure.
- FlowSwitch : In-built safety feature for the equipment unit shut off in case of cooling water failure.

[Read More](#)

SKU:

Price: ₹22,000.00

Stock: instock

Categories: [Water Still/Distillation Unit](#)

Product Description

It comprises of horizontal borosilicate glass boiler fitted with a 3 KW chromium plated immersion heater with cutoff, highly efficient coil condenser ensures a reliable output of single distillate. It is designed for easy usage, safe to operate and low cost. **Features**

Distillate Quality

Output	4ltr/h r
Conductivity	3 .0-4.0pS /cm
Distillate Quality	Pyrogen Free

Construction

- The stand is powder coated for long and rust free operation.
- The boiler and condenser are designed for high efficiency.
- Boiler is provided with Teflon Screw Cork for easy draining and cleaning of boiling chamber.
- Screw Threaded Connectors : These are provided for easy plumbing Et Installation to avoid any glassware breakage during assembly.
- For use on 220/240 V, 50/60Hz, Single Phase Supply.

Additional Optional Accessories (At Extra Cost)

- Gate Valve : Conserves cooling water wastage in case of power failure.
- Flow Switch : In-built safety feature for the equipment unit shut off in case of cooling water failure.



**WATER STILL
SHEATHED
(Still) Model
Cap. 2.0 ltr/
Consumption
Rating 3.0 k**

Water stills are carefully
purity pyrogen free
made from 3.3 exp.
horizontal type boiler

threaded connectors for ease of Cleaning.

- Distillate temperature is approx. between 25° to 45°C which is ensured by an condenser.
- The stand is powder coated for rust free operation and lustrous appearance.
- The unit automatically switches off if water level in the boiler falls below heater.
- Cooling water from the condenser is re-circulated into the boiling chamber, hence saving energy.
- Drain Stop Cork is provided for easy cleaning and maintenance.
- Electrical Power: 220/240 V, 50/60Hz, Single Phase Supply. **Unique Feature:** This model is equipped with in-built water level sensor to protect the Glass parts in case of water failure or overheating and buzzer is provided when user attention is required

Technical Specification Conductivity 0.8 to 1 $\mu\text{S}/\text{cm}$
Distillate Quality Pyrogen Free

[Read More](#)

SKU:

Price: ₹50,000.00

Stock: instock

Categories: [Water Still/Distillation Unit](#)

Product Description

Water stills are carefully designed to produce high purity pyrogen free distilled water. The water still made from 3.3 exp. borosilicate glass comprises of horizontal type boiler, condenser, constant level device, silica sheathed (Quartz) heater, along with stand and clamps. **Features:**

- Borosilicate condenser and boiler are with a removable silica sheathed heater and screw threaded connectors for ease of Cleaning.

energy.

- Drain Stop Cork is provided for easy cleaning and maintenance.
- Electrical Power: 220/240 V, 50/60Hz, Single Phase Supply. **Unique Feature:** This model is equipped with in-built water level sensor to protect the Glass parts in case of water failure or overheating and buzzer is provided when user attention is required

Technical Specification Conductivity 0.8 to 1 $\mu\text{S}/\text{cm}$ Distillate Quality Pyrogen Free



WATER STILL SHEATHED Still) Model Cap. (approx Cooling Wat 150 ltr/h, Po

Water stills are carefully designed to produce high purity pyrogen free distilled water. The unit is made from 3.3 exp. grade borosilicate glass, horizontal type boiler, stainless steel device, silica sheathed heating element, stand and clamps. It is equipped with a

- Borosilicate construction with removable silica sheathed heating element threaded connection
- Distillate temperature control at 45°C which is maintained by a thermostat
- The stand is polished and lustrous appearance
- The unit automatically shuts off the power in the boiler failure

- Electrical Power: 220/240 V, 50/60HZ, Single Phase Supply. **Unique Feature:** This model is equipped with in-built water level sensor to protect the Glass parts in case of water failure or overheating and buzzer is provided when user attention is required

Technical Specification Conductivity 0.8 to 1 $\mu\text{S}/\text{cm}$
Distillate Quality Pyrogen Free

[Read More](#)

SKU:

Price: ₹70,000.00

Stock: instock

Categories: [Water Still/Distillation Unit](#)

Product Description

Water stills are carefully designed to produce high purity pyrogen free distilled water. The water still made from 3.3 exp. borosilicate glass comprises of horizontal type boiler, condenser, constant level device, silica sheathed (Quartz) heater, along with stand and clamps. **Features:**

- Borosilicate condenser and boiler are with a removable silica sheathed heater and screw threaded connectors for ease of Cleaning.
- Distillate temperature is approx. between 25° to 45°C which is ensured by an condenser.
- The stand is powder coated for rust free operation and lustrous appearance.
- The unit automatically switches off if water level in the boiler falls below heater.
- Cooling water from the condenser is re-circulated into the boiling chamber, hence saving energy.
- Drain Stop Cork is provided for easy cleaning and maintenance.
- Electrical Power: 220/240 V, 50/60Hz, Single Phase Supply. **Unique Feature:** This model is equipped with in-built water level sensor to protect the Glass parts in case of water failure or overheating and buzzer is provided when user attention is required

Technical Specification Conductivity 0.8 to 1 $\mu\text{S}/\text{cm}$ Distillate Quality Pyrogen Free



2.0 ltr/hr, C Consumption Rating 1.5

Water stills are carefully designed to produce high purity pyrogen free distilled water. The unit is made from 3.3 exp. rated stainless steel. It has a horizontal type boiler. The unit is a compact device, silica sheathed, and is mounted on a stand and clamps. It is designed for use in a laboratory.

- Borosilicate condenser with removable silica sheath and threaded connections.
- Distillate temperature is maintained at 45°C which is suitable for most laboratory applications.
- The stand is polished and lustrous.
- The unit automatically shuts off the power to the boiler fan when the water level is low.
- Cooling water is circulated into the boiling chamber.
- Drain nozzle/Tap for cleaning and maintenance.
- Electrical Power: 230V, 50Hz, Single Phase.

Unique Feature:

This model is equipped with a safety feature of water failure cut-off.

[Read More](#)

SKU:

Product Description

Water stills are carefully designed to produce high purity pyrogen free distilled water. The water still made from 3.3 exp. borosilicate glass comprises of horizontal type boiler, condenser, constant level device, silica sheathed (Quartz) heater, along with stand and clamps. Features:

- Borosilicate condenser and boiler are fitted with a removable silica sheathed heater and screw threaded connectors for ease of Cleaning.
- Distillate temperature is approx. between 25° to 45°C which is ensured by an efficient
- The stand is powder coated for rust free operation and lustrous
- The unit automatically switches off if water level in the boiler falls below heater.
- Cooling water from the condenser is re-circulated into the boiling chamber, hence saving
- Drain nozzle/Tap on Stop Cork is provided for easy cleaning and maintenance.
- Electrical Power: 220/240 V, 50/60Hz, Single Phase

Unique Feature:

This model is equipped with in-built water level sensor to protect the Glass parts in case of water failure or overheating and buzzer is provided when user attention is required



**WATER STILL
SHEATHED
Model No. S
(approx) 4.0
Water Cons
Power Ratin**

Water stills are carefully designed to produce high purity pyrogen free distilled water. The water still made from 3.3 exp. borosilicate glass comprises of horizontal type boiler, constant level device, silica sheathed

- Distillate temperature is approx. between 25° to 45°C which is ensured by an efficient
- The stand is powder coated for rust free operation and lustrous
- The unit automatically switches off if water level in the boiler falls below heater.
- Cooling water from the condenser is re-circulated into the boiling chamber, hence saving
- Drain nozzle/Tap on Stop Cork is provided for easy cleaning and maintenance.
- Electrical Power: 220/240 V, 50/60Hz, Single Phase

Unique Feature:

This model is equipped with in-built water level sensor of water failure or overheating and buzzer is provided.

[Read More](#)

SKU:

Price: ₹40,000.00

Stock: instock

Categories: [Water Still/Distillation Unit](#)

Product Description

Water stills are carefully designed to produce high purity pyrogen free distilled water. The water still made from 3.3 exp. borosilicate glass comprises of horizontal type boiler, condenser, constant level device, silica sheathed (Quartz) heater, along with stand and clamps. Features:

- Borosilicate condenser and boiler are fitted with a removable silica sheathed heater and screw threaded connectors for ease of Cleaning.
- Distillate temperature is approx. between 25° to 45°C which is ensured by an efficient
- The stand is powder coated for rust free operation and lustrous
- The unit automatically switches off if water level in the boiler falls below heater.

This model is equipped with in-built water level sensor to protect the Glass parts in case of water failure or overheating and buzzer is provided when user attention is required

Water Table 3D Raised Relief Chart Framed On Board

(Any One Chart as Below) Educational Chart
(72x100CM)

[Read More](#)

SKU:

Price: ₹3,800.00

Stock: instock

Categories: [Geography & Surveying](#)



Product Description

(Any One Chart as Below) Educational Chart (72x100CM)

[Read More](#)

SKU:

Price: ₹1,800.00

Stock: instock

Categories: [Geography & Surveying](#)



Product Description

WATER TAP (SWAN NECK Type) Brass C.P. “AGN Make” One Way REGULAR

[Read More](#)

SKU:

Price: ₹950.00

Stock: instock

Categories: [Chemistry](#)



Product Description