











Capacity 50 Ltr/Hr, Consists of two plastic column charged with high exchange capacity Cation & Anion resins. Conductivity Meter Provided

Read More

SKU:

**Price:** ₹24,000.00

**Stock:** instock

**Categories:** Pharmacy

# **Product Description**

Capacity 50 Ltr/Hr, Consists of two plastic column charged with high exchange capacity Cation & Anion resins. Conductivity Meter Provided





TOT SIZE ZZATSCIII WE CHAIGE 750.00 NS OITIY

**Read More** 

SKU:

**Price:** ₹1,200.00

Stock: instock

Categories: Geography & Surveying



## **Product Description**

For Size 22x15cm we Charge 450.00 Rs only

# WATER LEVEL APPARATUS on Base



SKU:

**Price:** ₹130.00

**Stock:** instock

**Categories: Physics** 



## **Product Description**





Price: ₹450.00 Stock: instock

**Categories:** Chemistry



# **Product Description**



# WATER STII HEATER

It comprises of hori with a 3 KW chromi cutoff, highly efficie output of single dis safe to operate and

- Abundant Output
   distilled water
   Laboratory use
   pyrogen free of
- Distillate temp 40° C which is condenser.













- The stand is powder coated for long and rust free operation.
- The boiler and condenser are designed for high efficiency.
- Boiler is provided with Teflon Screw Cork for easy draining and cleaning of boiling chamber.
- Screw Threaded Connectors: These are provided for easy plumbing Et Installation to avoid any glassware breakage during assembly.
- For useon 220/240 V, 50/60Hz, Single Phase Supply.

## **Additional Optional Accessories (At Extra Cost)**

- Gate Valve : Conserves cooling water wastage in case of power failure.
- FlowSwitch : In-built safety feature for the equipment unit shut off in case of cooling water failure.

## Read More

SKU:

**Price:** ₹22,000.00

Stock: instock

Categories: Water Still/Distillation Unit

# **Product Description**

It comprises of horizontal borosilicate glass boiler fitted with a 3 KW chromium plated immersion heater with cutoff, highly efficient coil condenser ensures a reliable output of single distillate. It is designed for easy usage, safe to operate and low cost. Features











## **Distillate Quality**

Output 4ltr/h r

Cond uctivity 3 .0-4.0pS /cm

Disti llateQuality PyrogenFree

### Construction

- The stand is powder coated for long and rust free operation.
- The boiler and condenser are designed for high efficiency.
- Boiler is provided with Teflon Screw Cork for easy draining and cleaning of boiling chamber.
- Screw Threaded Connectors: These are provided for easy plumbing Et Installation to avoid any glassware breakage during assembly.
- For useon 220/240 V, 50/60Hz, Single Phase Supply.

## **Additional Optional Accessories (At Extra Cost)**

- Gate Valve: Conserves cooling water wastage in case of power failure.
- FlowSwitch: In-built safety feature for the equipment unit shut off in case of cooling water failure.



**WATER STIL** SHEATHED Still) Model Cap. 2.0 ltr/ Consumption Rating 3.0

Water stills are care purity pyrogen free made from 3.3 exp horizontal type boil















- Distillate temperature is approx. between 25° to 45°C which is ensured by an condenser.
- The stand is powder coated for rust free operation and lustrous appearance.
- The unit automatically switches off if water level in the boiler falls below heater.
- Cooling water from the condenser is re-circulated into the boiling chamber, hence saving energy.
- Drain Stop Cork is provided for easy cleaning and maintenance.
- Electrical Power: 220/240 V, 50/60Hz, Single Phase Supply. **Unique Feature:** This model is equipped with in-built water level sensor to protect the Glass parts in case of water failure or overheating and buzzer is provided when user attention is required

Technical Specification Conductivity 0.8 to 1 µs/cm Distillate Quality Pyrogen Free

## Read More

SKU:

**Price:** ₹50,000.00

**Stock:** instock

Categories: Water Still/Distillation Unit

# **Product Description**

Water stills are carefully designed to produce high purity pyrogen free distilled water. The water still made from 3.3 exp. borosilicate glass comprises of horizontal type boiler, condenser, constant level device, silica sheathed (Quartz) heater, along with stand and clamps. Features:

 Borosilicate condenser and boiler are with a removable silica sheathed heater and screw threaded connectors for ease of Cleaning.

MANUFACTURER & SUPPLIED
ALL KINDS OF LABORATORY EQUIPMENTS



energy.

- Drain Stop Cork is provided for easy cleaning and maintenance.
- Electrical Power: 220/240 V, 50/60Hz, Single Phase Supply. **Unique Feature:** This model is equipped with in-built water level sensor to protect the Glass parts in case of water failure or overheating and buzzer is provided when user attention is required

Technical Specification Conductivity 0.8 to 1 µs/cm Distillate Quality Pyrogen Free



# WATER STILL SHEATHED Still) Model Cap. (approcooling Water 150 ltr/h, Po

Water stills are care purity pyrogen free made from 3.3 exp horizontal type boil device, silica sheat stand and clamps.

- Borosilicate co removable silie threaded conn
- Distillate temp
   45°C which is
- The stand is per and lustrous a
- The unit autor in the boiler fa















• Electrical Power: 220/240 V, 50/60Hz, Single Phase Supply. **Unique Feature:** This model is equipped with in-built water level sensor to protect the Glass parts in case of water failure or overheating and buzzer is provided when user attention is required

Technical Specification Conductivity 0.8 to 1 µs/cm Distillate Quality Pyrogen Free

## Read More

SKU:

**Price:** ₹70.000.00

Stock: instock

Categories: Water Still/Distillation Unit

## **Product Description**

Water stills are carefully designed to produce high purity pyrogen free distilled water. The water still made from 3.3 exp. borosilicate glass comprises of horizontal type boiler, condenser, constant level device, silica sheathed (Quartz) heater, along with stand and clamps. Features:

- Borosilicate condenser and boiler are with a removable silica sheathed heater and screw threaded connectors for ease of Cleaning.
- Distillate temperature is approx. between 25° to 45°C which is ensured by an condenser.
- The stand is powder coated for rust free operation and lustrous appearance.
- The unit automatically switches off if water level in the boiler falls below heater.
- Cooling water from the condenser is re-circulated into the boiling chamber, hence saving energy.
- Drain Stop Cork is provided for easy cleaning and maintenance.
- Electrical Power: 220/240 V, 50/60Hz, Single Phase Supply. Unique Feature: This model is equipped with in-built water level sensor to protect the Glass parts in case of water failure or overheating and buzzer is provided when user attention is required

Technical Specification Conductivity 0.8 to 1 µs/cm Distillate Quality Pyrogen Free

















# 2.0 ltr/hr, C Consumption Rating 1.5 I

'I I

Water stills are care purity pyrogen free made from 3.3 exp horizontal type boil device, silica sheat stand and clamps.

- Borosilicate co removable silie threaded conn
- Distillate temp 45°C which is
- The stand is pe and lustrous
- The unit auton in the boiler fa
- Cooling water into the boiling
- Drain nozzle/T cleaning and r
- Electrical Power Phase

**Unique Feature:** 

This model is equ of water failure of

**Read More** 

SKU:

MANUFACTURER & SUPPLIED
ALL KINDS OF LABORATORY EQUIPMENTS



## **Product Description**

Water stills are carefully designed to produce high purity pyrogen free distilled water. The water still made from 3.3 exp. borosilicate glass comprises of horizontal type boiler, condenser, constant level device, silica sheathed (Quartz) heater, along with stand and clamps. Features:

- Borosilicate condenser and boiler are •tted with a removable silica sheathed heater and screw threaded connectors for ease of Cleaning.
- Distillate temperature is approx. between 25° to 45°C which is ensured by an of cient
- The stand is powder coated for rust free operation and lustrous
- The unit automatically switches off if water level in the boiler falls below heater.
- Cooling water from the condenser is re-circulated into the boiling chamber, hence saving
- Drain nozzle/Te on Stop Cork is provided for easy cleaning and maintenance.
- Electrical Power: 220/240 V, 50/60Hz, Single Phase

## **Unique Feature:**

This model is equipped with in-built water level sensor to protect the Glass parts in cas of water failure or overheating and buzzer is provided when user attention is required



WATER STILL
SHEATHED
Model No. 5
(approx) 4.6
Water Cons
Power Ratio

Water stills are care purity pyrogen free made from 3.3 exp. horizontal type boil device, silica sheat















- Distillate temperature is approx. between 25° to 45°C which is ensured by an of cient
- The stand is powder coated for rust free operation and lustrous
- The unit automatically switches off if water level in the boiler falls below heater.
- Cooling water from the condenser is re-circulated into the boiling chamber, hence saving
- Drain nozzle/Te on Stop Cork is provided for easy cleaning and maintenance.
- Electrical Power: 220/240 V, 50/60Hz, Single Phase

## **Unique Feature:**

This model is equipped with in-built water level ser of water failure or overheating and buzzer is provide

Read More

SKU:

**Price:** ₹40,000.00

**Stock:** instock

Categories: Water Still/Distillation Unit

## **Product Description**

Water stills are carefully designed to produce high purity pyrogen free distilled water. The water still made from 3.3 exp. borosilicate glass comprises of horizontal type boiler, condenser, constant level device, silica sheathed (Quartz) heater, along with stand and clamps. Features:

- Borosilicate condenser and boiler are •tted with a removable silica sheathed heater and screw threaded connectors for ease of Cleaning.
- Distillate temperature is approx. between 25° to 45°C which is ensured by an of cient
- The stand is powder coated for rust free operation and lustrous
- The unit automatically switches off if water level in the boiler falls below heater.



This model is equipped with in-built water level sensor to protect the Glass parts in cas of water failure or overheating and buzzer is provided when user attention is required

# Water Table 3D Raised Relief Chart Framed On Board

(Any One Chart as Below) Educational Chart (72x100CM)

Read More

SKU:

**Price:** ₹3,800.00

**Stock:** instock

**Categories:** Geography & Surveying



# **Product Description**

(Any One Chart as Below) Educational Chart (72x100CM)















SKU:

**Price:** ₹1,800.00

Stock: instock

Categories: Geography & Surveying



# **Product Description**

# **WATER TAP (SWAN NECK Type)** Brass C.P. "AGN Make" One Way **REGULAR**



Read More

SKU:

**Price:** ₹950.00 Stock: instock

**Categories:** Chemistry

# **Product Description**