

[Read More](#)

**SKU:**

**Price:** ₹135,000.00

**Stock:** instock

**Categories:** [Biology](#)



## Product Description

### PICC Line (Peripherally Inserted Central Catheter)

[Read More](#)

**SKU:**

**Price:** ₹132,600.00

**Stock:** instock

**Categories:** [Biology](#)



## Product Description



## Features:

- Replaceable silicon jacket is fitted with screw threads
  - Distillate temperature is maintained at 45°C which is
  - The stand is polished and lustrous appearance
  - Cooling water inlet into the boiling chamber
  - Fuse is provided to prevent fluctuation or short circuit
  - Boiler is provided with Level Device for boiling chamber
- Features:
- Gate Valve: Controls the flow of water in case of power failure
  - Flow Switch: Interlocks the equipment unit in case of failure.
  - Temperature sensor: Monitors the safety temperature if water level is low, thus saving the



# AGN ENTERPRISES

MANUFACTURER & SUPPLIER  
ALL KINDS OF LABORATORY EQUIPMENTS



DD-25HM	2.5Ltr/Hr	5 KW
DD-35HM	3.5Ltr/Hr	6 KW
DD-40HM	4.0Ltr/Hr	7 KW
DD-50HM	5.0Ltr/Hr	8 KW

■ Indicates 3 Phase

\*\* It is recommended to use Water Softener Unit with All types of water  
distillate & long life.

\*\*\*pH electrodes will NOT give accurate pH values in distilled or deionized water  
water do not have enough ions present for the electrode to function properly  
meaningless. In practice, however, most distilled water will have a pH that is  
presence of carbon dioxide (CO<sub>2</sub>) that is absorbed from the atmosphere.

[Read More](#)

**SKU:**

**Price:** ₹130,000.00

**Stock:** instock

**Categories:** [Water Still/Distillation Unit](#)

## Product Description

### Features:

- Replaceable silica heater: The horizontal quartz jacket is fitted with removable silica heater and screw threaded connectors for ease of cleaning
- Distillate temperature is Approx Between 25°C to 45°C which is ensured by an efficient condenser.
- The stand is powder coated for rust free operation and lustrous appearance.
- Cooling water from the condenser is re-circulated into the boiling chamber, hence saving energy.
- Fuse is provided for safety in case of voltage fluctuation or short circuit.
- Boiler is provided with a Replaceable Constant Level Device for easy draining and cleaning of boiling chamber. Additional In-built Safety Features:
- Gate Valve: Conserves cooling water wastage in case of power failure.
- Flow Switch: In-built safety feature for the equipment unit shut off in case of cooling water failure.

	Output Capacity (Approx.)	Power Rating (Total)	Cooling Water Consumption (App.)	
DD-15HM	1.5Ltr/Hr	3 KW	50 Ltr/Hr	130000.00
DD-20HM	2.0Ltr/Hr	4 KW	65 Ltr/Hr	170000.00
DD-25HM	2.5Ltr/Hr	5 KW	70 Ltr/Hr	190000.00
DD-35HM	3.5Ltr/Hr	6 KW	90 Ltr/Hr	220000.00
DD-40HM	4.0Ltr/Hr	7 KW	120 Ltr/Hr	250000.00
DD-50HM	5.0Ltr/Hr	8 KW	150 Ltr/Hr	300000.00

■ Indicates 3 Phase

\*\* It is recommended to use Water Softener Unit with All types of water distillations for desired output, good quality distillate & long life.

\*\*\*pH electrodes will NOT give accurate pH values in distilled or deionized water. This is because distilled and deionized water do not have enough ions present for the electrode to function properly. The readings will drift and be essentially meaningless. In practice, however, most distilled water will have a pH that is slightly acidic (less than 7.0) due to the presence of carbon dioxide (CO<sub>2</sub>) that is absorbed from the atmosphere.

## ENVIRONMENTAL CHAMBER HUMIDITY CABINET Inside Chamber 605 x 605 x 605mm, Cap. 225 Ltr.

Temp. (5-50 Deg C) & Humidity Range 20-95%

[Read More](#)

**SKU:**

**Price:** ₹130,000.00

**Stock:** instock

**Categories:** [Biotechnology](#)



### Product Description



[Read More](#)

**SKU:**

**Price:** ₹130,000.00

**Stock:** instock

**Categories:** [Pharmacy](#)

## Product Description

## Prostate Inspection Model

[Read More](#)

**SKU:**

**Price:** ₹130,000.00

**Stock:** instock

**Categories:** [Biology](#)



## Product Description



[Read More](#)

**SKU:**

**Price:** ₹130,000.00

**Stock:** instock

**Categories:** [Chemistry](#)

## Product Description

## ORBITAL SHAKING INCUBATOR CUM- B.O.D. Incubator Temp. 5° above ambient to 60° C.



Cap. 16x500ml With Digital Temp. Indicator Cum Controller

[Read More](#)

**SKU:**

**Price:** ₹128,000.00

**Stock:** instock

**Categories:** [Biotechnology](#)

## Product Description

Cap. 16x500ml With Digital Temp. Indicator Cum Controller

**Price:** ₹127,800.00

**Stock:** instock

**Categories:** [Biology](#)



## Product Description

## Advanced Multi-Functional Child Nursing Manikin(unisex)

[Read More](#)

**SKU:**

**Price:** ₹127,000.00

**Stock:** instock

**Categories:** [Biology](#)



## Product Description





It has been designed to meet the requirements and expectations of the laboratory. All Quartz Double Distillation Unit consists of upper and lower boiler, heater enclosed in a stainless steel jacket. The upper boiler has a condensing unit with the help of ball and socket joint. The condenser ensures the coming from the two circuit. The unit in a powder coated stainless steel. Control Unit. This is designed for better distillation unit. It has an advanced microprocessor. This has the latest technology introduced by our company. machine interaction has been used shows all the running of the machine which beeps as and when. Special advantages

- Easy cleaning and dismantled from
- Ease of interchange Ball & Socket joint
- Boiler & condenser resulting in better of
- Compact and easy

## Parameters





# AGN ENTERPRISES

MANUFACTURER & SUPPLIER  
ALL KINDS OF LABORATORY EQUIPMENTS



Silica

'All the parameters are under Standard Test Conditions. P  
water before *use*. "We recommend a Quartz Reservoir for  
Water.

## Technical Specifications

	Output Capacity (Approx.)	Power Rating (Total)
DD-15AQ	1.5Ltr/Hr	3 KW
DD-25AQ	2.5Ltr/Hr	5 KW
DD-35AQ	3.5Ltr/Hr	7 KW
DD-40AQ	4.0Ltr/Hr	8 KW
DD-50AQ	5.0Ltr/Hr	9 KW

■ Indicates 3 Phase

• The above cost is inclusive of Safety Cut off Device

\*\* It is recommended to use Water Softener Unit with All types of Water dist  
output, good quality distillate and long life.

[Read More](#)

**SKU:**

**Price:** ₹120,000.00

**Stock:** instock



# AGN ENTERPRISES

MANUFACTURER & SUPPLIER  
ALL KINDS OF LABORATORY EQUIPMENTS



equipment. All Quartz Double Distillation consists of demountable upper and lower boiler. The lower boiler has a built-in heater enclosed in a quartz boiler with a cup on top. The upper boiler has a built-in quartz coil and condensing unit which is mounted on the boiler with the help of ball and socket joint. Double-walled condenser ensures separate condensation of vapors coming from the two boilers using a single cooling circuit. The unit is mounted on a specially designed powder-coated stand and is also provided with Safety Control Unit. This new dual-safety cut-off has been designed for better and accurate control of the distillation unit. It has been incorporated with advanced microprocessor-based electronic circuitry. This has the latest electronic technology that has been introduced by our company, which gives an easy user-machine interaction. The alpha-numeric LCD which has been used shows all messages that correspond to the running of the machine. Also, there is an alarm system which beeps as and when user attention is required. Special advantages of Demountable Model

- Easy cleaning of the first boiler since it can be dismantled from the assembly.
- Ease of interchangeability as it is provided with Ball & Socket joint.
- Boiler & condenser have larger boiling space resulting in balanced boiling & improved quality of
- Compact and easy to install.



# AGN ENTERPRISES

MANUFACTURER & SUPPLIER  
ALL KINDS OF LABORATORY EQUIPMENTS



Total Solids

0.1 mgffir

Silica

· 0.01 rrtgiltr

'All the parameters are under Standard Test Conditions. Please test the distilled water before use. "We recommend a Quartz Reservoir for storage of High Purity Water.

## Technical Specifications

	Output Capacity (Approx.)	Power Rating (Total)	Cooling Water Consumption (App.)	
DD-15AQ	1.5Ltr/Hr	3 KW	50 Ltrs/Hr	120000.00
DD-25AQ	2.5Ltr/Hr	5 KW	70 Ltrs/Hr	150000.00
DD-35AQ	3.5Ltr/Hr	7 KW	90 Ltrs/Hr	200000.00
DD-40AQ	4.0Ltr/Hr	8 KW	120 Ltrs/Hr	240000.00
DD-50AQ	5.0Ltr/Hr	9 KW	150 Ltrs/Hr	280000.00

■ Indicates 3 Phase

• The above cost is inclusive of Safety Cut off Device

\*\* It is recommended to use Water Softener Unit with All types of Water distillations for desired output, good quality distillate and long life.



[Read More](#)

**SKU:**

**Price:** ₹120,000.00

**Stock:** instock

**Categories:** [Biotechnology](#)

## Product Description