



Model)

Features:

- Replaceable silicon jacket is fitted with screw threaded
 - Distillate temperature is maintained at 45°C which is
 - The stand is polished and lustrous
 - Cooling water inlet into the boiling
 - Fuse is provided to prevent fluctuation or short
 - Boiler is provided with Level Device for boiling chamber
- Features:
- Gate Valve: Closes the case of power
 - Flow Switch: Interlocks equipment unit failure.
 - Temperature sensor safety temperature if water level is thus saving the



AGN ENTERPRISES

MANUFACTURER & SUPPLIER
ALL KINDS OF LABORATORY EQUIPMENTS



DD-25HM	2.5Ltr/Hr	5 KW
DD-35HM	3.5Ltr/Hr	6 KW
DD-40HM	4.0Ltr/Hr	7 KW
DD-50HM	5.0Ltr/Hr	8 KW

■ Indicates 3 Phase

** It is recommended to use Water Softener Unit with All types of water
distillate & long life.

***pH electrodes will NOT give accurate pH values in distilled or deionized water
water do not have enough ions present for the electrode to function properly
meaningless. In practice, however, most distilled water will have a pH that is
presence of carbon dioxide (CO₂) that is absorbed from the atmosphere.

[Read More](#)

SKU:

Price: ₹130,000.00

Stock: instock

Categories: [Water Still/Distillation Unit](#)

Product Description

Features:

- Replaceable silica heater: The horizontal quartz jacket is fitted with removable silica heater and screw threaded connectors for ease of cleaning
- Distillate temperature is Approx Between 25°C to 45°C which is ensured by an efficient condenser.
- The stand is powder coated for rust free operation and lustrous appearance.
- Cooling water from the condenser is re-circulated into the boiling chamber, hence saving energy.
- Fuse is provided for safety in case of voltage fluctuation or short circuit.
- Boiler is provided with a Replaceable Constant Level Device for easy draining and cleaning of boiling chamber. Additional In-built Safety Features:
- Gate Valve: Conserves cooling water wastage in case of power failure.
- Flow Switch: In-built safety feature for the equipment unit shut off in case of cooling water failure.

	Output Capacity (Approx.)	Power Rating (Total)	Cooling Water Consumption (App.)	
DD-15HM	1.5Ltr/Hr	3 KW	50 Ltr/Hr	130000.00
DD-20HM	2.0Ltr/Hr	4 KW	65 Ltr/Hr	170000.00
DD-25HM	2.5Ltr/Hr	5 KW	70 Ltr/Hr	190000.00
DD-35HM	3.5Ltr/Hr	6 KW	90 Ltr/Hr	220000.00
DD-40HM	4.0Ltr/Hr	7 KW	120 Ltr/Hr	250000.00
DD-50HM	5.0Ltr/Hr	8 KW	150 Ltr/Hr	300000.00

■ Indicates 3 Phase

** It is recommended to use Water Softener Unit with All types of water distillations for desired output, good quality distillate & long life.

***pH electrodes will NOT give accurate pH values in distilled or deionized water. This is because distilled and deionized water do not have enough ions present for the electrode to function properly. The readings will drift and be essentially meaningless. In practice, however, most distilled water will have a pH that is slightly acidic (less than 7.0) due to the presence of carbon dioxide (CO₂) that is absorbed from the atmosphere.

ALL QUARTZ DISTILLATION



It has been designed to meet all requirements and specifications for All Quartz Double Distillation. The upper and lower boiler heater enclosed in a stainless steel jacket. The upper boiler has a condensing unit with the help of ball and joint condenser ensures the coming from the two circuit. The unit is made of powder coated stainless steel. Control Unit. This unit is designed for better

machine interaction. The alpha numeric LCD which has been used shows all messages that correspond to the running of the machine. Also there is alarm system which beeps as and when user attention is required. Special advantages of Demountable Model

- Easy cleaning of the first boiler since it can be dismantled from the assembly.
- Ease of interchangeability as it is provided with Ball & Socket joint.
- Boiler & condenser have larger boiling space resulting in balanced boiling & improved quality of
- Compact and easy to install.

Parameters

Specific Conductivity

Biological Activity (distillate quality)

Organic Matter

Total Solids

Silica

Technical Specifications

	Output Capacity (Approx.)	Power Rating (Total)
DD-15AQ	1.5Ltr/Hr	3 KW
DD-25AQ	2.5Ltr/Hr	5 KW
DD-35AQ	3.5Ltr/Hr	7 KW
DD-40AQ	4.0Ltr/Hr	8 KW
DD-50AQ	5.0Ltr/Hr	9 KW

■ Indicates 3 Phase

• The above cost is inclusive of Safety Cut off Device

** It is recommended to use Water Softener Unit with All types of Water distillation output, good quality distillate and long life.

[Read More](#)

SKU:

Price: ₹120,000.00

Stock: instock

Categories: [Water Still/Distillation Unit](#)

Product Description

It has been designed keeping in view customer requirements and easy serviceability of the equipment. All Quartz Double Distillation consists of demountable upper and lower boiler. The lower boiler has a built in heater enclosed in a quartz boiler with a cup on top. The upper boiler has a built in quartz coil and condensing unit which is mounted on the boiler with the help of ball and socket joint. Double walled condenser ensures separate condensation of vapors coming from the two boilers using a single cooling circuit. The unit is mounted on a specially designed powder coated stand and is also provided with Safety Control Unit. This new dual - safety cut off has been designed for better and accurate control of the distillation unit. It has been incorporated with advanced microprocessor based electronic circuitry. This has the latest electronic technology that has been introduced by our company which gives an easy user machine interaction. The alpha numeric LCD which has been used shows all messages that correspond to the running of the machine. Also there is an alarm system which beeps as and when user attention is required. Special advantages of Demountable Model

- Easy cleaning of the first boiler since it can be dismantled from the assembly.



AGN ENTERPRISES

MANUFACTURER & SUPPLIER
ALL KINDS OF LABORATORY EQUIPMENTS



Parameters

Specific Conductivity
Biological Activity (distillate quality)
Organic Matter
Total Solids
Silica

Values

0.10.5 ps/cm
Pyrogen Free
Nil
0.1 mgffir
· 0.01 rrtgiltr

'All the parameters are under Standard Test Conditions. Please test the distilled water before use. "We recommend a Quartz Reservoir for storage of High Purity Water.

DD-35AQ	3.5Ltr/Hr	7 KW	90 Ltrs/Hr	200000.00
DD-40AQ	4.0Ltr/Hr	8 KW	120 Ltrs/Hr	240000.00
DD-50AQ	5.0Ltr/Hr	9 KW	150 Ltrs/Hr	280000.00

■ Indicates 3 Phase

- The above cost is inclusive of Safety Cut off Device
- ** It is recommended to use Water Softener Unit with All types of Water distillations for desired output, good quality distillate and long life.

SINGLE STAGE DISTILLATION (Model)

Features

- Distillate temperature controlled by efficient condenser
- operation lustrous
- Cooling water flow into boiling chamber
- provided in fluorescent
- Electrical Power Phase Supply.
- Boiler is provided with Constant Level cleaning of boiler



Unique Feature This unit has a temperature switch for protection of water failure or c

- Gate Valve : Conserves cooling water wastage in case of power
- Flow Switch : In-built safety feature for the equipment unit sh

Borosilicate Condenser

	Output Capacity (Approx.)	Power Rating (Total)
SD-20BH	2 Ltr/Hr	1.7 KW
SD-50BH	5 Ltr/Hr	3.4 KW

Quartz Condenser

	Output Capacity (Approx.)	Power Rating (Total)
SD-20QH	2 Ltr/Hr	1.7 KW
SD-50QH	5 Ltr/Hr	3.4 KW

[Read More](#)

SKU:

Price: ₹50,000.00

Stock: instock

Categories: [Water Still/Distillation Unit](#)

Product Description

Features

- Distillate temperature is between ensured by an efficient condenser.
- operation lustrous in boiler
- Cooling water from the condenser re-circulated into boiling chamber, hence saving energy.
- provided in fluctuation
- Electrical Power : 220/240 V, 50/60Hz, Single Phase Supply.
- Boiler is provided with Replaceable Quartz ConstantLevel Device for easy draining and cleaning of boiling chamber.

Unique Feature This model is equipped with in-built temperature switch to protect the Glass parts in case of water failure or overheating.

- Gate Valve : Conserves cooling water wastage in case of power failure.
- Flow Switch : In-built safety feature for the equipment unit shut off in case of cooling water failure.

Borosilicate Condenser

	Output Capacity (Approx.)	Power Rating (Total)	Cooling Water Consumption (App.)	
SD-20BH	2 Ltr/Hr	1.7 KW	35 Ltr/Hr	50000.00
SD-50BH	5 Ltr/Hr	3.4 KW	70 Ltr/Hr.	80000.00

Quartz Condenser

	Output Capacity (Approx.)	Power Rating (Total)	Cooling Water Consumption (App.)	
SD-20QH	2 Ltr/Hr	1.7 KW	35 Ltr/Hr	64000.00
SD-50QH	5 Ltr/Hr	3.4 KW	70 Ltr/Hr.	120000.00

SINGLE STAGE DISTILLATION

The apparatus consists of a high purity quartz with built-in cleaning of deposits. It features a boiler with receiving vessel, Safety Control Unit, and various parts in case of water failure. It can withstand thermal shock proof.



"AU the parameters are under Standard Test Conditions' Advantages

- Rust proof powder coated sturdy stand as
- Replaceable clamps are provided for

alignment of the boiler and condenser. Advanced Feattres

- Distillate is pyrogen free; also it is free of heavy metals.
- Switch on time is less than minute providing distilled water instantly.
- Low maintenance is



AGN ENTERPRISES

MANUFACTURER & SUPPLIER
ALL KINDS OF LABORATORY EQUIPMENTS



Quartz Condenser

	Output Capacity (Approx.)	Power Rating (Total)	Cooling Water
SD-25Q	2.5Ltr/Hr	2 KW	40 Ltr/Hr
SD-50Q	5 Ltr/Hr	4.4 KW	65 Ltr/Hr
SD-80Q	8 Ltr/Hr	6 KW	90 Ltr/Hr
SD-100Q	10 Ltr/Hr	9 KW	120 Ltr/Hr

■ Indicates 3 Phase

Safety Cut Off Device (Digital Safety Control Unit with Alarm)

SCU-1	2 Ltr/Hr
SCU-2	5,8 & 10 Ltr/Hr

** It is recommended to use Water Softener Unit with All types of water distillations for desired output, good quality distillate & long life.

[Read More](#)

SKU:

Price: ₹36,000.00

Stock: instock

Categories: [Water Still/Distillation Unit](#)

Product Description

The apparatus consists of a boiler made from high purity quartz with built in discharge joint for easy cleaning of deposits. A spiral condenser is fitted on the boiler with receiving adapter. The unit comes with Safety Control Unit (Optional) to protect the Glass parts in case of water failure or overheating. Quartz can withstand high temperature and is thus thermal shock proof.

"AU the parameters are under Standard Test Conditions' Advantages

- Rust proof powder coated sturdy stand as
- Replaceable clamps are provided for

alignment of the boiler and condenser. Advanced Feattres

- Distillate is pyrogen free; also it is free of heavy metals.
- Switch on time is less than minute providing distilled water instantly.
- Low maintenance is

Borosilicate Condenser

	Output Capacity (Approx.)	Power Rating (Total)	Cooling Water Consumption (App.)	
SD-25B	2.5Ltr/Hr	2 KW	40 Ltr/Hr	36000.00
SD-50B	5 Ltr/Hr	4.4 KW	65 Ltr/Hr.	60000.00
SD-80B	8 Ltr/Hr	6 KW	90 Ltr/Hr	86000.00
SD-100B	10 Ltr/Hr	9 KW	120 Ltr/Hr	100000.00

Quartz Condenser

	Output Capacity (Approx.)	Power Rating (Total)	Cooling Water Consumption (App.)	
SD-25Q	2.5Ltr/Hr	2 KW	40 Ltr/Hr	55000.00
SD-50Q	5 Ltr/Hr	4.4 KW	65 Ltr/Hr.	100000.00
SD-80Q	8 Ltr/Hr	6 KW	90 Ltr/Hr	130000.00
SD-100Q	10 Ltr/Hr	9 KW	120 Ltr/Hr	180000.00

■ Indicates 3 Phase

Safety Cut Off Device (Digital Safety Control Unit with Alarm)

SCU-1	2 Ltr/Hr	20000.00
SCU-2	5,8 &10 Ltr/Hr	22000.00

** It is recommended to use Water Softener Unit with All types of water distillations fo
desired output, good quality distillate & long life.



Compact & User Friendly
water distillation equipment
research laboratories
from 3.3 exp borosil
distillation has following

- Replaceable silicon
horizontal quartz
silica Sheathed
connectors for
- Distillate temperature
45°C which is
- The stand is polished
and lustrous a
- Cooling water
into the boiling
- Screw Threaded
for easy plumbing
glassware break
- Fuse is provided
fluctuation or s
- Boiler is provided
Flow for easy c
chamber.
- The front cover
access to the g
- Electrical Power
Phase Supply.
- Gate Valve: Co
case of power
- Flow Switch: In
equipment uni
failure.

- **Level Sensor:** It shuts off the Distillation equipment if the water level in the boiler falls below the heater.
- **Reservoir Level Sensor:** This helps in automatic working of the water distillation equipment. Depending on the water level in the reservoir it will automatically switch On/Off the equipment, thus saving energy. (Reservoir can also be provided with a storage capacity of 5 ltr, 10 ltr & 20 ltr made of Borosilicate Glass or polypropylene)

Borosilicate Glass

	CM-20S	CM-20D	CM-40
Output Capacity (Approx.)	2 Ltr/Hr	2 Ltr/Hr	4 Ltr/Hr
Stage	Single Stage	Double Stage	Single Stage

Distillate Quality	Pyrogen Free	Pyrogen Free	Pyrogen Free
Conductivity $\mu\text{S/cm}$	1.0 - 2.0	0.8 - 1.0	1.0
Cooling Water Requirement (Approx)	1.5 Ltr/min	2 Ltr/min	2-3
Power Rating (Total)	1.5 KW	3.0 KW	3.0
Price/Pc	54000.00	80000.00	70000.00

**All the parameters are under Standard Test Conditions.

**Output quality would depend upon the quality of inlet feed water.

[Read More](#)

SKU:

Price: ₹54,000.00

Stock: instock

Categories: [Water Still/Distillation Unit](#)

Product Description

Compact & User Friendly This is a fully automatic water distillation equipment and can be used in research laboratories, hospitals etc. It is manufactured from 3.3 exp borosilicate glass or quartz glass. The distillation has following features:

- The stand is powder coated for rust free operation and lustrous appearance.
- Cooling water from the condenser is re-circulated into the boiling chamber, hence saving energy.
- Screw Threaded Connectors: These are provided for easy plumbing & Installation to avoid any glassware breakage during assembly.
- Fuse is provided for safety in case of voltage fluctuation or short circuit.
- Boiler is provided with a Replaceable Side Over Flow for easy draining and cleaning of boiling chamber.
- The front cover is easily removable making the access to the glass parts very easy.
- Electrical Power: 220/240 V, 50/60Hz, Single Phase Supply. Additional In-built Safety Features:
 - Gate Valve: Conserves cooling water wastage in case of power failure.
 - Flow Switch: In-built safety feature for the equipment unit shut off in case of cooling water failure.
 - Temperature switch: The boiler is equipped with a safety temperature switch which shuts off the unit if water level in the boiler falls below the heater, thus saving the glass parts from any damages.
 - Level Sensor: It Shuts off the Distillation equipment if the water level in the boiler falls below the heater.
 - Reservoir Level Sensor: This helps in automatic working of the water distillation equipment. Depending on the water level in the reservoir it will automatically switch On/Off the equipment, thus saving energy. (Reservoir can also be provided with a storage capacity of 5 ltr, 10 ltr & 20 ltr made of Borosilicate Glass or polypropylene)

Borosilicate Glass

	CM-20S	CM-20D	CM-40S	CM-40D
Output Capacity (Approx.)	2 Ltr/Hr	2 Ltr/Hr	4 Ltr/Hr	4 Ltr/Hr
Stage	Single Stage	Double Stage	Single Stage	Double Stage
Distillate Quality	Pyrogen Free	Pyrogen Free	Pyrogen Free	Pyrogen Free
Conductivity $\mu\text{S/cm}$	1.0 - 2.0	0.8 - 1.0	1.0 - 2.0	0.8 - 1.0
Cooling Water Requirement (Approx)	1.5 Ltr/min	2 Ltr/min	2-3Ltr/min	2-4 Ltr/min
Power Rating (Total)	1.5 KW	3.0 KW	3.0 KW	6.0 KW
Price/Pc	54000.00	80000.00	70000.00	120000.00

**All the parameters are under Standard Test Conditions.

**Output quality would depend upon the quality of inlet feed water.



Still) Model Cap. (approx Cooling Wat 150 ltr/h, Po

Water stills are care
purity pyrogen free
made from 3.3 exp
horizontal type boi
device, silica sheath
stand and clamps. I

- Borosilicate co
removable silic
threaded conn
- Distillate temp
45°C which is
- The stand is po
and lustrous a
- The unit autom
in the boiler fa
- Cooling water
into the boiling
- Drain Stop Cor
maintenance.
- Electrical Powe
Phase Supply.
equipped with
protect the Gla
overheating an
attention is rec

Technical Specifica

Stock: instock**Categories:** [Water Still/Distillation Unit](#)

Product Description

Water stills are carefully designed to produce high purity pyrogen free distilled water. The water still made from 3.3 exp. borosilicate glass comprises of horizontal type boiler, condenser, constant level device, silica sheathed (Quartz) heater, along with stand and clamps. **Features:**

- Borosilicate condenser and boiler are with a removable silica sheathed heater and screw threaded connectors for ease of Cleaning.
- Distillate temperature is approx. between 25° to 45°C which is ensured by an condenser.
- The stand is powder coated for rust free operation and lustrous appearance.
- The unit automatically switches off if water level in the boiler falls below heater.
- Cooling water from the condenser is re-circulated into the boiling chamber, hence saving energy.
- Drain Stop Cork is provided for easy cleaning and maintenance.
- Electrical Power: 220/240 V, 50/60Hz, Single Phase Supply. **Unique Feature:** This model is equipped with in-built water level sensor to protect the Glass parts in case of water failure or overheating and buzzer is provided when user attention is required

Technical Specification Conductivity 0.8 to 1 $\mu\text{S}/\text{cm}$ Distillate Quality Pyrogen Free



Cap. 2.0 ltr/ Consumption Rating 3.0 k

Water stills are carefully designed to produce high purity pyrogen free distilled water. The unit is made from 3.3 exp. grade borosilicate glass, horizontal type boiler, stainless steel support device, silica sheathed heating element, stand and clamps. It is suitable for use in the laboratory.

- Borosilicate construction, removable silica sheathed heating element, threaded connections.
- Distillate temperature controlled at 45°C which is suitable for most laboratory purposes.
- The stand is polished and lustrous appearance.
- The unit automatically shuts off the power in the boiler failure.
- Cooling water inlet and outlet into the boiling chamber.
- Drain Stop Control for easy maintenance.
- Electrical Power Supply, Phase Supply. The unit is equipped with a safety feature to protect the Glassware from overheating and attention is required.

Technical Specifications
Distillate Quality Pyrogen Free



Categories: [Water Still/Distillation Unit](#)

Product Description

Water stills are carefully designed to produce high purity pyrogen free distilled water. The water still made from 3.3 exp. borosilicate glass comprises of horizontal type boiler, condenser, constant level device, silica sheathed (Quartz) heater, along with stand and clamps. **Features:**

- Borosilicate condenser and boiler are with a removable silica sheathed heater and screw threaded connectors for ease of Cleaning.
- Distillate temperature is approx. between 25° to 45°C which is ensured by an condenser.
- The stand is powder coated for rust free operation and lustrous appearance.
- The unit automatically switches off if water level in the boiler falls below heater.
- Cooling water from the condenser is re-circulated into the boiling chamber, hence saving energy.
- Drain Stop Cork is provided for easy cleaning and maintenance.
- Electrical Power: 220/240 V, 50/60Hz, Single Phase Supply. **Unique Feature:** This model is equipped with in-built water level sensor to protect the Glass parts in case of water failure or overheating and buzzer is provided when user attention is required

Technical Specification Conductivity 0.8 to 1 $\mu\text{S}/\text{cm}$ Distillate Quality Pyrogen Free



(approx) 4.0 Water Cons Power Ratin

Water stills are carefully designed to produce high purity pyrogen free distilled water. The unit is made from 3.3 exp. grade borosilicate glass. It has a horizontal type boiler. The unit is a self-contained device, silica sheathed, and requires no external stand and clamps. It is designed for compact design.

- Borosilicate construction with removable silica sheath and threaded connections.
- Distillate temperature is maintained at 45°C which is suitable for most laboratory applications.
- The stand is polished and lustrous.
- The unit automatically shuts off the power in the boiler fan.
- Cooling water is circulated into the boiling chamber.
- Drain nozzle/Tap for cleaning and maintenance.
- Electrical Power: 230V, 50Hz, Single Phase.

Unique Feature:

This model is equipped with a safety feature of water failure cut-off.

[Read More](#)

SKU:

Product Description

Water stills are carefully designed to produce high purity pyrogen free distilled water. The water still made from 3.3 exp. borosilicate glass comprises of horizontal type boiler, condenser, constant level device, silica sheathed (Quartz) heater, along with stand and clamps. Features:

- Borosilicate condenser and boiler are fitted with a removable silica sheathed heater and screw threaded connectors for ease of Cleaning.
- Distillate temperature is approx. between 25° to 45°C which is ensured by an efficient
- The stand is powder coated for rust free operation and lustrous
- The unit automatically switches off if water level in the boiler falls below heater.
- Cooling water from the condenser is re-circulated into the boiling chamber, hence saving
- Drain nozzle/Tap on Stop Cork is provided for easy cleaning and maintenance.
- Electrical Power: 220/240 V, 50/60Hz, Single Phase

Unique Feature:

This model is equipped with in-built water level sensor to protect the Glass parts in case of water failure or overheating and buzzer is provided when user attention is required



**WATER STILL
SHEATHED
Model No. S
2.0 ltr/hr, C
Consumption
Rating 1.5 ltr**

Water stills are carefully designed to produce high purity pyrogen free distilled water. The water still made from 3.3 exp. borosilicate glass comprises of horizontal type boiler, condenser, constant level device, silica sheathed

- Distillate temperature is approx. between 25° to 45°C which is ensured by an efficient
- The stand is powder coated for rust free operation and lustrous
- The unit automatically switches off if water level in the boiler falls below heater.
- Cooling water from the condenser is re-circulated into the boiling chamber, hence saving
- Drain nozzle/Tap on Stop Cork is provided for easy cleaning and maintenance.
- Electrical Power: 220/240 V, 50/60Hz, Single Phase

Unique Feature:

This model is equipped with in-built water level sensor of water failure or overheating and buzzer is provided.

[Read More](#)

SKU:

Price: ₹30,000.00

Stock: instock

Categories: [Water Still/Distillation Unit](#)

Product Description

Water stills are carefully designed to produce high purity pyrogen free distilled water. The water still made from 3.3 exp. borosilicate glass comprises of horizontal type boiler, condenser, constant level device, silica sheathed (Quartz) heater, along with stand and clamps. Features:

- Borosilicate condenser and boiler are fitted with a removable silica sheathed heater and screw threaded connectors for ease of Cleaning.
- Distillate temperature is approx. between 25° to 45°C which is ensured by an efficient
- The stand is powder coated for rust free operation and lustrous
- The unit automatically switches off if water level in the boiler falls below heater.

This model is equipped with in-built water level sensor to protect the Glass parts in case of water failure or overheating and buzzer is provided when user attention is required

WATER STILL HEATER



It comprises of horizontal glass coil with a 3 KW chromi cutoff, highly efficient output of single dist safe to operate and

- Abundant Output of distilled water for Laboratory use, pyrogen free
- Distillate temperature 40° C which is safe to operate and

Distillate Quality

Output

Cond uctivity

Disti llateQuality

Construction

- The stand is provided for easy operation.
- The boiler and condenser are made of high efficiency.
- Boiler is provided with draining and c



AGN ENTERPRISES

MANUFACTURER & SUPPLIER
ALL KINDS OF LABORATORY EQUIPMENTS



Supply.

Additional Optional Accessories (At Extra Cost)

- Gate Valve : Conserves cooling water wastage in case of power failure.
- FlowSwitch : In-built safety feature for the equipment unit shut off in case of cooling water failure.

[Read More](#)

SKU:

Price: ₹22,000.00

Stock: instock

Categories: [Water Still/Distillation Unit](#)

Product Description

It comprises of horizontal borosilicate glass boiler fitted with a 3 KW chromium plated immersion heater with cutoff, highly efficient coil condenser ensures a reliable output of single distillate. It is designed for easy usage, safe to operate and low cost. **Features**

- Abundant Output : The still provides 4 ltr/hr of distilled water which is ideal for General Laboratory use and is capable for producing pyrogen free distillate.
- Distillate temperature is approx. between 25° - 40° C which is ensured by highly efficient condenser.

Distillate Quality

Output	4ltr/h r
Cond uctivity	3 .0-4.0pS /cm
Disti llateQuality	PyrogenFree

Construction

- The stand is powder coated for long and rust free operation.

- For use on 220/240 V, 50/60HZ, Single Phase Supply.

Additional Optional Accessories (At Extra Cost)

- Gate Valve : Conserves cooling water wastage in case of power failure.
- FlowSwitch : In-built safety feature for the equipment unit shut off in case of cooling water failure.

CRUCIBLES WITHOUT LID 50ml


[Read More](#)

SKU:

Price: ₹920.00

Stock: instock

Categories: [Quartz Glassware](#)



Product Description

CRUCIBLES WITHOUT LID 25ml


[Read More](#)

SKU:

Price: ₹580.00

Stock: instock

Categories: [Quartz Glassware](#)



Product Description