



## Quality (In Thermocole Box)

[Read More](#)

**SKU:**

**Price:** ₹1,100.00

**Stock:** instock

**Categories:** [Biology](#)

## Product Description

## POLARIMETER “AGN Make Bi-Quartz

[Read More](#)

**SKU:**

**Price:** ₹6,400.00

**Stock:** instock

**Categories:** [Physics](#)



## Product Description

**Price:** ₹12,000.00

**Stock:** instock

**Categories:** [Pharmacy](#)



## Product Description

### PASCAL LAW (Glass) “AGN Make”

[Read More](#)

**SKU:**

**Price:** ₹140.00

**Stock:** instock

**Categories:** [Physics](#)



## Product Description



**Price:** ₹12.00

**Stock:** instock

**Categories:** [Physics](#)

## Product Description

## AUTOMATIC BOMB CALORIMETER AGN-800

[Read More](#)

**SKU:**

**Price:**

**Stock:** instock

**Categories:** [Laboratory Equipments](#)



## Product Description

**SALIENT FEATURES**

- \* Display Calorific Value in Calorie/gram or other internationally accepted units.
- \* Extensive Diagnostic Function for problem investigation.
- \* Integrated and closed loop water handling system.
- \* "auto shut off" of the filling valve after attaining of requisite pressure in the bomb.
- \* Automatic compensation of calorific value to get ready made GCV in Cal/gm. or Kcal/Kg.
- \* Double stage SS gas regulators with safety valve.
- \* Branded on line UPS with 60

Power : 220V, 50HZ single phase AC. Sample weight : (0.6 to 1.4) gram. CV Range : upto 8,000 Kcal/Kg for 1 gram of sample. CV Resolution : 0.1 Calorie/gram. Precision : 0.05 % RSD on Benzoic acid for GCV. Temperature Resolution : 0.0001 degree centigrade. Analysis Time : Maximum 15 minutes. Balance analysis sample : 0.0001 gram. Connecting tube : 2 meter length. Cylinder : Filled Oxygen 47 Litre. UPS Warranty : 2 years from the date of installation.

**ACCESSORIES :** \* Branded PC. \* Printer. \* Fuse Wire - 10,000 Numbers. \* O-ring. \* Combustion Crucible -20 Nos with each set. \* Tool Kit. \* Bomb charging station . \* Bomb wiping cloth . \* Dust Cover. \* Instruction Manual. \* Warranty Card.

## BIO SAFETY CABINET CLASS II, TYPE B2 (CLASS 100) AGN-59-12

[Read More](#)

**SKU:**

**Price:**

**Stock:** instock

**Categories:** [Laboratory Equipments](#)



### Product Description

#### SALIENT FEATURES:

\* Single piece made of SS 304 work top, both side and front chamber wall with curve corner.



# AGN ENTERPRISES

MANUFACTURER & SUPPLIER  
ALL KINDS OF LABORATORY EQUIPMENTS



\* Single piece work tray.

\* 100% Exhaust, a support stand provide with lockable caster wheels.

## **TECHNICAL PARAMETERS:-**

Model : AGN-59-12

Internal work area dimensions : 4' x 2' x 2' (L x H x D)

HEPA Filter : Dual HEPA Filter 99.999% for particles >0.3µm.

Inner Working Chamber : SS 304 (Stainless Steel)

Outer Cabinet body : GI Sheet Fabrication finished with powder coated.

Velocity : 90FPM  $\pm$ 20%

Door Sensor : 50% Blower switch off and while light switch on automatically

Blower : Highly efficient centrifugal type with lifetime lubricated bearings.

UV Hours : UV life hours be displayed, door is open UV light cut-off

Noise level : <55dba

Fluorescent lamp intensity : High intensity, low wattage >800LUX

Casters : 4 nos. with moveable positions.

Power Supply : 230  $\pm$  10V, Single Phase 50Hz.

Motor Blower : Electronically Commutated Motor

Accessories : Illumination Light, UV light, inside socket (16A), gas/air cock burner, vacuum port.

Certification : ISO Certified & Test Report



[Read More](#)

**SKU:**

**Price:**

**Stock:** instock

**Categories:** [Applied Mechanics](#)

## Product Description

**Specifications** \* Easy to clean, non-polluting. \* Paddle scientifically and reasonably structured. \* Smooth operation, saving time and power. \* Interlock safety device. \* Mixing Speed control. \* Movable castors, easy to move. \* Motor with overload protection to protect itself. **Technical Parameters:-** Material for Tank / Drum : S.S. Plate. Motor with Gearbox : 10H.P.(With Starter Panel). Mixing Capacity : 200 Kg per Batch. Mixing Timing : up to 60 minutes. Power Supply : 420/440V 50 Hz., 3 Phase.





**Price:**

**Stock:** instock

**Categories:** [Applied Mechanics](#), [Laboratory Equipments](#)

## Product Description

**Short Form Specification** Four Plate hot plate electric oven. Electric characteristics to be \_\_400V or \_\_230V. Unit to be installed on stainless steel feet with height adjustment up to 50 mm. Unit to have cast-iron hot plates hermetically sealed to the one-piece top. Oven chamber with 3 levels of runners to accomodate 2/1 GN shelves (2 steam pans). Unit to have ribbed, cast-iron oven base plate. Exterior panels of unit in Stainless steel with Scotch Brite finish. Extra strength work top in heavy duty 2 mm Stainless steel. Unit has right-angled side edges to allow flush-fitting junction between units. **Construction:-** Unit is 930 mm deep to give a larger working surface area. All exterior panels in Stainless Steel with Scotch Brite finishing. AISI 304 stainless steel worktop, 2mm thick. Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps. **Main Features** • Unit to be mounted on stainless steel feet with height adjustment up to 50 mm. Unit can be easily mounted on cantilever systems. • The four 4kW electric cast-iron hot plates are hermetically sealed to the one piece top and are featured with safety thermostat. • Base compartment consists of an electric heat insulation, positioned beneath the base plate. • Oven chamber with 3 levels of runners to accomodate 2/1 shelves (2 steam pans). • Ribbed cast iron oven base

Oven thermostat adjustable from 100 °C to 300°C Included Accessories • 1 chrome grid for static oven • 1 chrome grid for static oven Pair of cast iron plate bars for electric cooking top • Junction sealing kit • Kit 4 wheels - 2 swivelling with brake - it is mandatory to install Base support and wheels • Flanged feet kit • Frontal kicking strip for concrete installation, 800mm

## HIGH SPEED MIXER UNIT AGN-SMU-24

[Read More](#)

**SKU:**

**Price:**

**Stock:** instock

**Categories:** [Applied Mechanics](#)



### Product Description

**Salient Features:-** \* High Speed Mixer Unit Fabricated from Heavy Duty angles and channels \* Mixing Vessel Fabricated from Heavy duty plates lines with heavy gauge Stainless steel material 304 grade \* Water jacketing provision for effective cooling of the material \* 8 to 10 min for batch \* Mixing knives mounted on suitable angle that it mixes material homogeneously and preheats the same to the required temperature \* Mixing drum enclosure will be of thick SS plate \* Temperature sensor provided on baffle which will be of SS material \* Digital temperature indicator provided to indicate mixing temperature. \* Suitable for mixing of Plastic granules with colorants and powder additives **Technical Parameters:-** 24" x 24" Mixer Machine (with 20HP



## MUFFLE FURNACE AGN-MF-55

[Read More](#)

**SKU:**

**Price:**

**Stock:** instock

**Categories:** [Laboratory Equipments](#), [Pathology](#), [Physics](#)



### Product Description

**Salient Features:** \* P Type thermocouple for long term stability. \* The light gauge overband heating elements is embedded. \* The equipment is thermal Insulation Material. \* Horizontal side swing door. \* 1" diameter at the top of the unit and air inlet of 0.375" diameter. \* This equipment is safety door switch will interupted power to heating element door is opened. \* The fast heating System room temp. to 1200°C in 45min. \* 300 min for the chamber cool down from 1200°C to 200°C. \* Average Temp. on the outer housing 41°C the ambient is at 23°C ambient. \* Programs patterns can be based either time on rate. \* LCD display trend recording function , graphic prompts, configurable display data. **Product Specification:** Working Temperature Range : 1200°C Chamber Size : 55L Interior Dimension : 15" x 15" x 15" Exterior Dimension : 28" x 29" x 33" Uniformity :  $\pm 2.0^{\circ}\text{C}$  Ambient Temp. : 23°C Exterior Body Material : Powder Coated old rolled steel Programs : 5 Programs up to 16 Segments for ramp (up and down) Program Steps : 999times Display : Large 5 digit LED Display. Over Temp. Protection Facility : YES Power Supply : 240V, 50Hz. Warranty : 1 Year



[Read More](#)

**SKU:**

**Price:**

**Stock:** instock

**Categories:** [Chemistry](#)

## Product Description

**DESCRIPTION:** Pharmaceutical Refrigerators offer a complete solution for the most demanding requirements for storage of pharmaceuticals, medicines, vaccines, and other temperature-sensitive applications. Model Number : AGN LR-554 External dimensions (W x D x H) : 900 x 650 x 1824mm Internal dimensions (W x D x H) : 800 x 510 x 1425mm Volume : 554L Net weight : 140 (Kg) **Performance** Temperature control range : +2 to +14°C Cooling System : Hermetic rotary compressor 250Watt. **Control** Controller : Microcomputer Control System Temp. Controller : Fan Forced Air circulation. Display : Digital display (in 1°C, 0.1°C increments) Temperature sensor : Thermistor sensor **Refrigeration** Cooling method : Forced cool air circulation Defrost method : Cyclical defrost + forced defrost Refrigerant : R-600a Insulation :



# AGN ENTERPRISES

MANUFACTURER & SUPPLIER  
ALL KINDS OF LABORATORY EQUIPMENTS



Back Access port diameter : 30mm Casters ; 4 NOS. Interior Illumination : LED Light

**Accessories.** Key : x2. Electrical and Noise Level Power supply : 230V / 50 Hz. Noise level : 42dbA.