



Model No. S (approx) 4.0 Water Cons Power Ratin

Water stills are carefully designed to produce high purity pyrogen free distilled water. The unit is made from 3.3 exp. grade borosilicate glass. It has a horizontal type boiler with a heating element, a silica sheathed thermocouple, a drain nozzle, a stand and clamps. It is a compact design.

- Borosilicate construction with removable silica sheathed thermocouple and threaded connections.
- Distillate temperature is maintained at 45°C which is suitable for most laboratory purposes.
- The stand is made of stainless steel and is lustrous.
- The unit automatically shuts off the power in the boiler fan.
- Cooling water is circulated into the boiling chamber.
- Drain nozzle/Terminal for cleaning and maintenance.
- Electrical Power: 230V, 50Hz, Single Phase.

Unique Feature:
This model is equipped with a safety feature of water failure cut-off.

[Read More](#)



AGN ENTERPRISES

MANUFACTURER & SUPPLIER
ALL KINDS OF LABORATORY EQUIPMENTS



Categories: [Water Still/Distillation Unit](#)

Product Description

Water stills are carefully designed to produce high purity pyrogen free distilled water. The water still made from 3.3 exp. borosilicate glass comprises of horizontal type boiler, condenser, constant level device, silica sheathed (Quartz) heater, along with stand and clamps. Features:

- Borosilicate condenser and boiler are fitted with a removable silica sheathed heater and screw threaded connectors for ease of Cleaning.
- Distillate temperature is approx. between 25° to 45°C which is ensured by an efficient
- The stand is powder coated for rust free operation and lustrous
- The unit automatically switches off if water level in the boiler falls below heater.
- Cooling water from the condenser is re-circulated into the boiling chamber, hence saving
- Drain nozzle/Tap on Stop Cork is provided for easy cleaning and maintenance.
- Electrical Power: 220/240 V, 50/60Hz, Single Phase

Unique Feature:

This model is equipped with in-built water level sensor to protect the Glass parts in case of water failure or overheating and buzzer is provided when user attention is required