



Still) Model Cap. (approx Cooling Wat 150 ltr/h, Po

Water stills are care
purity pyrogen free
made from 3.3 exp
horizontal type boi
device, silica sheath
stand and clamps. I

- Borosilicate co
removable silic
threaded conn
- Distillate temp
45°C which is
- The stand is po
and lustrous a
- The unit autom
in the boiler fa
- Cooling water
into the boiling
- Drain Stop Cor
maintenance.
- Electrical Powe
Phase Supply.
equipped with
protect the Gla
overheating an
attention is rec

Technical Specifica

Stock: instock**Categories:** [Water Still/Distillation Unit](#)

Product Description

Water stills are carefully designed to produce high purity pyrogen free distilled water. The water still made from 3.3 exp. borosilicate glass comprises of horizontal type boiler, condenser, constant level device, silica sheathed (Quartz) heater, along with stand and clamps. **Features:**

- Borosilicate condenser and boiler are with a removable silica sheathed heater and screw threaded connectors for ease of Cleaning.
- Distillate temperature is approx. between 25° to 45°C which is ensured by an condenser.
- The stand is powder coated for rust free operation and lustrous appearance.
- The unit automatically switches off if water level in the boiler falls below heater.
- Cooling water from the condenser is re-circulated into the boiling chamber, hence saving energy.
- Drain Stop Cork is provided for easy cleaning and maintenance.
- Electrical Power: 220/240 V, 50/60Hz, Single Phase Supply. **Unique Feature:** This model is equipped with in-built water level sensor to protect the Glass parts in case of water failure or overheating and buzzer is provided when user attention is required

Technical Specification Conductivity 0.8 to 1 $\mu\text{S}/\text{cm}$ Distillate Quality Pyrogen Free
