



SKU:

Price: ₹375,000.00 Original price was: ₹375,000.00. ₹350,000.00 Current price is: ₹350,000.00.

Stock: instock

Categories: [Chemistry](#)

Product Description

It comes with modern and sophisticated features, one of which is its capacity to show rapid temperature and humidity changes according to input settings. They can cool down impressively, with high precision, enabling you to carry out complex climate tests. Through the digital display (Temperature, weekdays, time, humidity, automatic fan speed, programer status and set-up values-language) with Audio-Visual Alarm you can see all the parameters such as temperature inside as well as the humidity levels. The ingenuity of the design that it is capable of stable operation over long periods of time, even in situations wherein the illuminated chambers are filled with samples. **Its features include:**

- International quality standards and suitable for most of environmental conditions
- These Environmental Chamber are doubled walled constructed and has proper locking arrangement for SS 304 door is capable of simulating a wide rage of temperature and humidity conditions with Polystyrene Foam insulated.
- Compact in designed which enables you to place it in small space and use with ease.
- Is designed according to international quality standards hence you can be rest assured of high quality performance.
- Inclusive of secure locking system so that contents are safe and secure inside.
- Humidity inside is created with steam injected into the working chamber.
- Energy efficient and show safe and reliable performance in maintaining temperature as required in research environments. You will find our environment chamber to be just the thing needed to test materials under dynamic conditions. It has the capacity to control complex temperature at



AGN ENTERPRISES

MANUFACTURER & SUPPLIER
ALL KINDS OF LABORATORY EQUIPMENTS



dimension : 410W X 300d X 300h Exterior dimension : 758W X 645d X 1110h Display :
Programmable digital touch screen Shelves : SS Wire Mesh Refrigerant : CFC Free R-404 non
flammable (hermetically sealed single stage refrigeration system Temperature Range : -20°C to
+150°C $\pm 0.2^\circ\text{C}$ Humidity Range : 20% to 98% $\pm 1\%$ Access Port : Dia 50mm Pull Down time :
+40°C to 20°C within 35 mins Heat up time : -20°C to +150°C within 35 mins Water Tank
Capacity : 5 liters Calibration : Yes Data Logger : Yes Works on : 220/240VAC, Single Phase